

A large, stylized letter 'A' is formed using the characters 'S' and 'Y'. The 'S' characters are arranged in a grid-like pattern to form the left and right sides of the letter, while 'Y' characters form the central vertical stem and the diagonal crossbars. The overall shape is a bold, blocky 'A' that fills most of the page.

(4)	235	DECLARATIONS
(4)	428	CONTROL PARAMETERS
(4)	428	SYSTEM MESSAGE PARAMETERS
(4)	428	SYSTEM LOADABLE CODE PARAMETERS
(4)	428	TERMINAL DRIVER SYSTEM PARAMETERS
(4)	428	RMS DEFAULT PARAMETERS
(4)	428	FILE ACP CONFIGURATION DATA
(4)	428	Job Controller Parameters
(4)	428	Login Security Parameters
(4)	428	Cluster Parameters
(4)	466	SYSGETSYI - GETSYI main program
(4)	626	CHECKITEM - Validate item identifier
(4)	748	PUTDATA - Put requested data in user buffer
(4)	847	SPECIAL - Handle special conditions
(5)	1078	NAMCSID - Get specified node CSID
(6)	1227	EXESNAMCSID - CONVERT NODE NAME TO CSID

```
0000 1 .TITLE SYSGETSYI - GET SYSTEM INFORMATION SYSTEM SERVICE
0000 2 .IDENT 'V04-000'
0000 3 :
0000 4 :*****
0000 5 :
0000 6 :* COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
0000 7 :* DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
0000 8 :* ALL RIGHTS RESERVED.
0000 9 :
0000 10 :* THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
0000 11 :* ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
0000 12 :* INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
0000 13 :* COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
0000 14 :* OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
0000 15 :* TRANSFERRED.
0000 16 :
0000 17 :* THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
0000 18 :* AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
0000 19 :* CORPORATION.
0000 20 :
0000 21 :* DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
0000 22 :* SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
0000 23 :
0000 24 :
0000 25 :*****
0000 26 :
0000 27 :++
0000 28 : FACILITY: VMS Executive, System services.
0000 29 :
0000 30 : ABSTRACT:
0000 31 :
0000 32 : Return processor information to caller, specifically
0000 33 : processor ID register, processor type, and VMS version number.
0000 34 :
0000 35 : ENVIRONMENT: Kernel Mode
0000 36 :
0000 37 : AUTHOR: John A. Ywoskus, CREATION DATE: 06-August-1981
0000 38 :
0000 39 : MODIFIED BY:
0000 40 :
0000 41 : V03-026 CWH3026 CW Hobbs 23-Jul-1984
0000 42 : Treat the QUANTUM item as special, since it is
0000 43 : stored as a negative number.
0000 44 :
0000 45 : V03-025 MSH0059 Michael S. Harvey 3-Jul-1984
0000 46 : Treat a specified CSID argument of zero as if the argument
0000 47 : hadn't been specified at all. In either case, there is no
0000 48 : CSID value specified and the behavior of GETSYI should be
0000 49 : the same for both.
0000 50 :
0000 51 : V03-024 MSH0021 Michael S. Harvey 9-Mar-1984
0000 52 : Allow access to SYI items stashed away in the local SB,
0000 53 : regardless of whether we're in a cluster or not.
0000 54 :
0000 55 : V03-023 MSH0013 Michael S. Harvey 2-Mar-1984
0000 56 : Correctly extract node name length so as not to clobber
0000 57 : P1 space and crash the system.
```


0000	58	:			
0000	59	:	V03-022	WMC0003 Wayne Cardoza	9-Feb-1984
0000	60	:		Add \$ARCDEF.	
0000	61	:			
0000	62	:	V03-021	WMC0002 Wayne Cardoza	29-Jan-1984
0000	63	:		Add F and G floating flags.	
0000	64	:			
0000	65	:	V03-020	KPL0001 Peter Lieberwirth	15-Jan-1984
0000	66	:		Fix typo in V03-019.	
0000	67	:			
0000	68	:	V03-019	WMC0001 Wayne Cardoza	07-Jan-1984
0000	69	:		Add page and swap file sizes.	
0000	70	:			
0000	71	:	V03-018	TCM0001 Trudy C. Matthews	28-Dec-1983
0000	72	:		In EXESNAMCSID, do not access node name passed by caller	
0000	73	:		after raising IPL (it may be payable). Make QUORUM a	
0000	74	:		special parameter; it is stored as a negative value but should	
0000	75	:		be displayed as a positive one.	
0000	76	:			
0000	77	:	V03-017	KFH0011 Ken Henderson	30 Aug 1983
0000	78	:		Fix resetting of IPL on error path.	
0000	79	:		Add documentation of how	
0000	80	:		itemcodes are added.	
0000	81	:			
0000	82	:	V03-016	KFH0010 Ken Henderson	23 Aug 1983
0000	83	:		Fix checking of item code validity.	
0000	84	:		Update max structure code.	
0000	85	:			
0000	86	:	V03-015	KFH0009 Ken Henderson	18 Aug 1983
0000	87	:		Made SCS_EXISTS special and boolean.	
0000	88	:			
0000	89	:	V03-014	KFH0008 Ken Henderson	28 Jul 1983
0000	90	:		Finished support for 'retired' item-codes.	
0000	91	:		Took out call to SCS\$CONFIG_SYS.	
0000	92	:			
0000	93	:	V03-013	KFH0007 Ken Henderson	12 Jul 1983
0000	94	:		Added temporary additional check for	
0000	95	:		clusterness.	
0000	96	:			
0000	97	:	V03-012	KFH0006 Ken Henderson	26 May 1983
0000	98	:		Changed EXESNAMCSID entry point to	
0000	99	:		be non-Global.	
0000	100	:			
0000	101	:	V03-011	KFH0005 Ken Henderson	25 May 1983
0000	102	:		Updated code to use IFCLSTR and IFNOCLSTR.	
0000	103	:			
0000	104	:	V03-010	KFH0004 Ken Henderson	21 May 1983
0000	105	:		Added support for wild-carding through	
0000	106	:		nodes. Added NAMCSID and EXESNAMCSID routines.	
0000	107	:		Cleaned up usage of LOCAL_SPACE on stack.	
0000	108	:			
0000	109	:	V03-009	KFH0003 Ken Henderson	11 Mar 1983
0000	110	:		Added .WARN if item-code is undefined.	
0000	111	:			
0000	112	:	V03-008	KFH0002 Ken Henderson	25 Feb 1983
0000	113	:		Added definition of GETSYISW.	
0000	114	:			

0000	115	:	V03-007	KFH0001	Ken Henderson	16 Feb 1983
0000	116	:			Major rewrite of EXESGETSYI and related	
0000	117	:			routines to make it table-driven like GETJPI,	
0000	118	:			and allow for SYSBOOT parameters and other	
0000	119	:			enhancements.	
0000	120	:				
0000	121	:	V03-006	MSH0001	Maryann Hinden	23-Mar-1982
0000	122	:			Fix broken BSBW.	
0000	123	:				
0000	124	:	V03-005	JAY0006	John A. Ywoskus	17-Mar-1982
0000	125	:			Change SSS_EXQUOTA return error to SSS_EXASTLM.	
0000	126	:				
0000	127	:	V03-004	JAY0005	John A. Ywoskus	21-Jan-1982
0000	128	:			Return 8 bytes for system version instead of 4.	
0000	129	:			General cleanup.	
0000	130	:				
0000	131	:	V02-003	LJK0082	Lawrence J. Kenah	11-Nov-1981
0000	132	:			Write accessibility of multiple page buffer can	
0000	133	:			now be done on global routine.	
0000	134	:				
0000	135	:	V03-002	JAY0004	John A. Ywoskus	05-Oct-1981
0000	136	:			Add null arguments so call list is compatable with	
0000	137	:			\$GETJPI. Also, make external references be	
0000	138	:			addressed with G^, and include VA and PSL defs.	
0000	139	:				
0000	140	:	V03-001	JAY0003	John A. Ywoskus	08-Sep-1981
0000	141	:			Fix null item bug, make return length optional.	
0000	142	--				
0000	143	:				


```

0000 145 :          GUIDE TO GETJPI/GETSYI/GETDVI
0000 146 :          -----
0000 147 :
0000 148 : Overview
0000 149 : -----
0000 150 :
0000 151 : These three system services are table-driven. The macro definition files
0000 152 : that help define their tables are shared with DCL and the RTL. This results
0000 153 : in new item-codes becoming useable with DCL's FSGETXXI lexical functions and
0000 154 : the RTL's LIB$GETXXI routines automatically. Additionally, new SYSBOOT
0000 155 : parameters become item-codes to the GETSYIs.
0000 156 :
0000 157 : The macro definition files are called JPITABLE.MAR, SYITABLE.MAR, and
0000 158 : DVITABLE.MAR, and live in MASDS:<VMSLIB.SRC>. During a systembuild, they
0000 159 : are inserted into the library SYS$LIBRARY:SYSBLDMLB.MLB. DCL and the RTL
0000 160 : and SYS use this library to define their GETXXI tables. The system
0000 161 : parameter file <SYS.SRC>SYSPARAM.MAR has also been conditionalized to be
0000 162 : used to define GETSYI item-codes and is also inserted into SYSBLDMLB.MLB.
0000 163 :
0000 164 :
0000 165 : NOTE: SYSBLDMLB.MLB is a general macro library for holding macro
0000 166 : definitions that are shared between facilities, but will not
0000 167 : ship to the customer.
0000 168 :
0000 169 :
0000 170 : When adding an item-code, at least two files need to be edited. One of the
0000 171 : macro files listed above, as well as an SDL file that defines the 16-bit
0000 172 : number which is the user-visible item-code. Also, if a SYSBOOT parameter is
0000 173 : added, an SDL file needs to be updated to define the new GETSYI item-code.
0000 174 :
0000 175 : The GETDVI service actually uses only one table, but the GETSYI and GETJPI
0000 176 : services use several. The JPITABLE file defines all the tables for GETJPI
0000 177 : and the SYITABLE file defines all the tables for GETSYI. The different
0000 178 : tables group the pieces of data according to method of retrieval.
0000 179 :
0000 180 : In some cases, the piece of data to be returned by the service requires
0000 181 : special processing to fetch, calculate, or format it before returning it.
0000 182 : In these cases, the code of the system service needs to be enhanced.
0000 183 : If the data returned is a new format for DCL, the lexical function
0000 184 : module of DCL may need to be enhanced. This is also true for the RTL code.

```

```

0000 186 ;The Macros
0000 187 ;-----
0000 188 ;
0000 189 ;A two-level scheme exists for defining the item tables used by the three
0000 190 ;services and the other facilities. A commonly defined macro (called
0000 191 ;JPI GENERATE TABLE, SYI GENERATE TABLE, or DVI GENERATE TABLE) contains
0000 192 ;multiple calls to a lower-level macro (called JPI_ITEM_CODE, SYI_ITEM_CODE,
0000 193 ;or DVI_ITEM_CODE) which actually defines each element in the table.
0000 194 ;While the GENERATE TABLE macros are commonly defined, the ITEM_CODE macros
0000 195 ;are individually defined according to the needs of facility. (For instance,
0000 196 ;the LEXICON module must store the name of the item as an ASCII string - in
0000 197 ;order to match it with the string supplied in the FSGETXXI function call;
0000 198 ;the other facilities need not store the item name in text.)
0000 199 ;
0000 200 ;When an item-code must be added, an additional call to the ITEM_CODE macro
0000 201 ;must be added to the appropriate GENERATE TABLE macro. In the case of GETJPI
0000 202 ;and GETDVI, the GENERATE TABLE macro is defined in the JPITABLE and DVITABLE
0000 203 ;modules. The SYI GENERATE TABLE macro is defined by the SYSPARAM module
0000 204 ;- all the calls to the PARAMETER and PQL macros are 'collected' into the
0000 205 ;SYI GENERATE TABLE macro. When used in that mode (when GETSYISW is defined),
0000 206 ;the SYI_ITEMTABLES macro also becomes part of the SYI GENERATE TABLE macro.
0000 207 ;SYI_ITEMTABLES is defined in the SYITABLE module and contains all the calls
0000 208 ;to the SYI_ITEM_CODE macro that are Not related to SYSBOOT parameters.
0000 209 ;When GETSYISW is defined in SYSPARAM, the PARAMETER macro does not allocate
0000 210 ;or store memory, but rather passes some of the arguments to it on through via
0000 211 ;a call to SYI_ITEM_CODE. That is how all the calls to PARAMETER become calls
0000 212 ;to SYI_ITEM_CODE.
0000 213 ;
0000 214 ;The following is the situation that exists when the symbol GETSYISW is defined.
0000 215 ;The non-SYSBOOT items are defined by the macro SYI_ITEMTABLES in SYITABLE.MAR.
0000 216 ;The SYSBOOT items are defined by each invocation of the PARAMETER macro in
0000 217 ;SYSPARAM.MAR. Note that each invocation of the PQL macro in SYSPARAM.MAR
0000 218 ;invokes the PARAMETER macro twice. When GETSYISW is defined, the PARAMETER
0000 219 ;macro merely passes its arguments through to a call to the SYI_ITEM_CODE
0000 220 ;macro. The SYI_ITEM_CODE macro is locally defined as needed by the facility.
0000 221 ;
0000 222 ;-----
0000 223 ;
0000 224 ;
0000 225 ;
0000 226 ;
0000 227 ;
0000 228 ;
0000 229 ;
0000 230 ;
0000 231 ;
0000 232 ;
0000 233 ;

```

SYI_ITEMTABLES	SYI_GENERATE_TABLE	
	PARAMETER	PARAMETER PQL PARAMETER
SYI_ITEM_CODE	SYI_ITEM_CODE	SYI_ITEM_CODE

FROM SYITABLE.MAR
(NON-SYSBOOT ITEMS)

FROM SYSPARAM.MAR
(SYSBOOT ITEMS)


```
0000 235      .SBTTL  DECLARATIONS
0000 236      $ARCDDEF      ; architectural flags
0000 237      $CLUBDEF      ; cluster block definitions
0000 238      $CSBDEF      ; cluster system block definitions
0000 239      $IPLDEF      ; IPL definitions
0000 240      $PCBDEF      ; define processor control block
0000 241      $PFLDEF      ; page file control block
0000 242      $PRDEF      ; define processor registers
0000 243      $PSLDEF      ; define processor status register
0000 244      $SBDEF      ; system block definitions
0000 245      $SSDEF      ; define status codes
0000 246      $SYIDEF      ; define GETSYI item identifiers
0000 247      $VADEF      ; virtual addressing definitions
0000 248
0000 249
0000 250      :: Define the following symbol so that SYSPARAM macros will conditionalize
0000 251      :: correctly for us.
0000 252      ::
00000000 0000 253      GETSYISW = 0
0000 254
0000 255      ::
0000 256      :: MACROS:
0000 257      ::
0000 258
0000 259      ::
0000 260      :: Macros to define entries in the four item information tables.
0000 261      :: There is a table for each data structure from which the user may
0000 262      :: request information, and one table for information returned as an
0000 263      :: address. Tables are indexed by low byte of item identifier.
0000 264      :: Refer to 'OWN STORAGE:' for pictures of the table entries.
0000 265      ::
0000 266
0000 267      .MACRO  SYI_ITEM_CODE  BASE,-      ; for service to use
0000 268      NAME,-      ; of the item-code
0000 269      SOURCE,-      ; of the data
0000 270      DTYPE,-      ; of returned value
0000 271      BITPOS,-      ; of FLD type data
0000 272      BITSIZ,-      ;
0000 273      OUTLEN      ; of returned value
0000 274
0000 275      .IF NOT_DEFINED SYIS_'NAME
0000 276
0000 277      .IF IDENTICAL <BASE><EXE>
0000 278
0000 279      .WARN ; SYIS_'NAME IS NOT DEFINED AS 'EXE' IN STARDEFQZ.SDL
0000 280
0000 281      .ENDC ; IDENTICAL
0000 282
0000 283      .IF IDENTICAL <BASE><FLD>
0000 284
0000 285      .WARN ; SYIS_'NAME IS NOT DEFINED AS 'FLD' IN STARDEFQZ.SDL
0000 286
0000 287      .ENDC ; IDENTICAL
0000 288
0000 289      .ENDC ; NOT_DEFINED
0000 290
0000 291      STEP = 5
```



```
0000 292      .IIF IDENTICAL <BASE><EXE>,      STEP = 5
0000 293      .IIF IDENTICAL <BASE><FLD>,      STEP = 7
0000 294
0000 295      XTYPE = VALUE
0000 296      .IIF IDENTICAL <DTYPE><HEXNUM>, XTYPE = VALUE
0000 297      .IIF IDENTICAL <DTYPE><DECNUM>, XTYPE = VALUE
0000 298      .IIF IDENTICAL <DTYPE><PRVMSK>, XTYPE = VALUE
0000 299      .IIF IDENTICAL <DTYPE><PADSTR>, XTYPE = BSTRING
0000 300      .IIF IDENTICAL <DTYPE><HEXSTR>, XTYPE = BSTRING
0000 301      .IIF IDENTICAL <DTYPE><CNTSTR>, XTYPE = CSTRING
0000 302      .IIF IDENTICAL <DTYPE><STRDSC>, XTYPE = VALUE
0000 303      .IIF IDENTICAL <DTYPE><BITVEC>, XTYPE = VALUE
0000 304      .IIF IDENTICAL <DTYPE><BITVAL>, XTYPE = VALUE
0000 305      .IIF IDENTICAL <DTYPE><STDUIC>, XTYPE = VALUE
0000 306      .IIF IDENTICAL <DTYPE><STDTIM>, XTYPE = VALUE
0000 307
0000 308      . = BASE'TBL + <<SYS$_'NAME & ^XFFF> * STEP>
0000 309
0000 310      .IIF IDENTICAL <BASE><FLD>, .WORD <BITSIZ-1>@11!BITPOS
0000 311
0000 312      .LONG SOURCE
0000 313      .BYTE XTYPE@5!OUTLEN
0000 314
0000 315      .ENDM SYI_ITEM_CODE
0000 316
0000 317 :
0000 318 : This macro defines the entries to the table of special items.
0000 319 : The items in this table must be handled by action routines
0000 320 : before being returned. Each entry has a word item identifier
0000 321 : followed by the address of an action routine.
0000 322 : ALL PROCESSOR REGISTER ITEMS ARE SPECIALS.
0000 323 :
0000 324 :
0000 325      .MACRO SPECIAL_ITEM NAME,ROUTINE
0000 326      .WORD SYS$_'NAME
0000 327      .ADDRESS ROUTINE
0000 328      .ENDM SPECIAL_ITEM
0000 329
0000 330 :
0000 331 : This macro defines flag bits.
0000 332 :
0000 333 :
0000 334      .MACRO SYIBITS NAME,SIZE
0000 335      SYI_V_'NAME' = SYI_BIT
0000 336      SYI_S_'NAME' = SIZE
0000 337      SYI_BIT = SYI_BIT + SIZE
0000 338      .ENDM SYIBITS
0000 339
0000 340 :
0000 341 : EQUATED SYMBOLS:
0000 342 :
0000 343 :
00000004 0000 344      EFN = 4 ; event flag number argument
00000008 0000 345      NULLARG1 = 8 ; first null argument
0000000C 0000 346      NULLARG2 = 12 ; second null argument
00000010 0000 347      ITMLST = 16 ; address of item identifiers
00000014 0000 348      IOSB = 20 ; I/O status block address
```



```
00000018 0000 349      ASTADR  = 24      ; ast routine address
0000001C 0000 350      ASTPRM  = 28      ; ast parameter
00000002 0000 351      MAXSTRUC = 2      ; maximum structure code
00000000 0000 352      VALUE   = 0      ; datatypes
00000001 0000 353      BSTRING = 1
00000002 0000 354      CSTRING = 2
FFFFFFFFE0 0000 355      LOCAL_SPACE = -32      ; 8 longwords on stack
FFFFFFFFE0 0000 356      BITSIZ  = LOCAL_SPACE+0
FFFFFFFFE4 0000 357      BITPOS   = LOCAL_SPACE+4
FFFFFFFFE8 0000 358      TEMPORARY = LOCAL_SPACE+8
FFFFFFFFEC 0000 359      SPECIAL_SPACE = LOCAL_SPACE+12
FFFFFFFFFC 0000 360      FLAGS    = LOCAL_SPACE+28
           0000 361
           0000 362 :
           0000 363 : Bit definitions for flags longword on stack
           0000 364 :
           0000 365 :
00000000 0000 366      SYI_BIT = 0
           0000 367      SYIBITS WILD,1      ; we're doing a wildcard operation
           0000 368      SYIBITS INCLUSTER,1  ; we're in a live cluster
           0000 369      SYIBITS REMOTE_NODE,1 ; the target node isn't the local node
           0000 370      SYIBITS RETIRED,1    ; the item-code isn't in use anymore
           0000 371
           0000 372 :
           0000 373 : Max structure number definitions
           0000 374 :
           0000 375 :
00000101 0000 376      MAX_EXE_ITEM = <SYI$_LASTEXE&^XFFF>-1 ; maximum EXE item number
0000002A 0000 377      MAX_FLD_ITEM = <SYI$_LASTFLD&^XFFF>-1 ; maximum FLD item number
           0000 378
           0000 379 :
           0000 380 : OWN STORAGE:
           0000 381 :
           0000 382 :
00000000 0000 383      .PSECT YF$$$SYSGETSYI
           0000 384
           0000 385 :
           0000 386 : This array contains the maximum item number for each of the two
           0000 387 : item data structures, indexed by structure number.
           0000 388 :
           0000 389 MAXCOUNT:
0101 0000 390      .WORD MAX_EXE_ITEM
002A 0002 391      .WORD MAX_FLD_ITEM
           0004 392
```

```
0004 394 :  
0004 395 : The following tables are zeroed explicitly to allow the code to  
0004 396 : recognize an uninitialized element (because of a retired item-code)  
0004 397 :  
0004 398  
0004 399 EXETBL:  
0004 400 :-----  
0004 401 : .LONG SOURCE  
0004 402 : .BYTE DTYPE@5!OUTLEN  
0004 403 :-----  
0004 404  
0004 405 .REPEAT 5*<MAX_EXE_ITEM+1>  
0004 406 .BYTE 0  
00 0004 407 .ENDR  
050E 408  
050E 409 FLDTBL:  
050E 410 :-----  
050E 411 : .WORD <BITSIZ-1>@11!BITPOS  
050E 412 : .LONG SOURCE  
050E 413 : .BYTE DTYPE@5!OUTLEN  
050E 414 :-----  
050E 415  
050E 416 .REPEAT 7*<MAX_FLD_ITEM+1>  
050E 417 .BYTE 0  
00 050E 418 .ENDR  
063B 419  
063B 420 .SAVE  
063B 421  
063B 422 :*****  
063B 423 :  
063B 424 : GENERATE THE TABLES USING THE COMMONLY DEFINED MACRO  
063B 425 :  
063B 426 :*****  
063B 427  
063B 428 SYI_GENERATE_TABLE
```



```

0243
0243
0243      .NLIST CND
0243      PARAMETER      ADDRESS=EXESGL_DEFFLAGS,-
0243                      DEFAULT=1,-
0243                      MAX=1,-
0243                      MIN=0,-
0243                      NAME=BUGREBOOT,-
0243                      BIT=EXESV_BUGREBOOT,-
0243                      TYPE=<DYNAMIC,SYS>,-
0243                      UNIT=Boolean
00000004 0243      OUTLEN = 4
0243      SYI_ITEM_CODE  FLD,-
0243                      <BUGREBOOT>,-
0243                      <EXESGL_DEFFLAGS>,-
0243                      BITVAL,-
0243                      <EXESV_BUGREBOOT>,-
0243                      1,-
0243                      1
0243
00000005 0243      STEP = 5
0243
00000000 0243      XTYPE = VALUE
0243
00000515 0243      . = FLDTBL + <<SYIS_BUGREBOOT & ^XFFF> * STEP>
0515
00000000' 0517
01         051B      .LONG  EXESGL_DEFFLAGS
051C      .BYTE  XTYPE@5!1
051C
051C

```

```
03F6 429
0000063B 430 .RESTORE
063B 431
063B 432 :
063B 433 : Table to define items which must be handled by action routines
063B 434 :
063B 435
063B 436 SPECIAL:
063B 437 SPECIAL_ITEM CLUSTER_MEMBER, SPC_MEMBER
0641 438 SPECIAL_ITEM CLUSTER_NODES, SPC_CLUB
0647 439 SPECIAL_ITEM CLUSTER_VOTES, SPC_CLUB
064D 440 SPECIAL_ITEM CLUSTER_QUORUM, SPC_CLUB
0653 441 SPECIAL_ITEM CLUSTER_FSYSID, SPC_CLUB
0659 442 SPECIAL_ITEM CLUSTER_FTIME, SPC_CLUB
065F 443 SPECIAL_ITEM NODE_CSTD, SPC_CSB
0665 444 SPECIAL_ITEM NODE_VOTES, SPC_CSB
066B 445 SPECIAL_ITEM NODE_QUORUM, SPC_CSB
0671 446 SPECIAL_ITEM NODE_SYSTEMID, SPC_SB
0677 447 SPECIAL_ITEM NODE_AREA, SPC_SB
067D 448 SPECIAL_ITEM NODE_NUMBER, SPC_SB
0683 449 SPECIAL_ITEM NODE_SWINCARN, SPC_SB
0689 450 SPECIAL_ITEM NODE_SWTYPE, SPC_SB
068F 451 SPECIAL_ITEM NODE_SWVERS, SPC_SB
0695 452 SPECIAL_ITEM NODE_HWTYPE, SPC_SB
069B 453 SPECIAL_ITEM NODE_HWVERS, SPC_SB
06A1 454 SPECIAL_ITEM NODENAME, SPC_SB
06A7 455 SPECIAL_ITEM SCS_EXISTS, SPC_EXISTS
06AD 456 SPECIAL_ITEM SID, SPC_PROCREG
06B3 457 SPECIAL_ITEM CPU, SPC_PROCREG
06B9 458 SPECIAL_ITEM PAGEFILE_PAGE, SPC_PAGESWAP
06BF 459 SPECIAL_ITEM SWAPFILE_PAGE, SPC_PAGESWAP
06C5 460 SPECIAL_ITEM PAGEFILE_FREE, SPC_PAGESWAP
06CB 461 SPECIAL_ITEM SWAPFILE_FREE, SPC_PAGESWAP
06D1 462 SPECIAL_ITEM QUANTUM, SPC_NEGATIVE
0000001A 06D7 463 SPECIAL_LEN = <.-SPECIAL>/6
06D7 464
```



```
06D7 466 .SBTTL SYSGETSYI - GETSYI main program
06D7 467
06D7 468 :++
06D7 469
06D7 470 : FUNCTIONAL DESCRIPTION:
06D7 471
06D7 472 : This service allows a process to receive status and identification
06D7 473 : information about the system on which the calling process is running.
06D7 474
06D7 475 : CALLING SEQUENCE:
06D7 476
06D7 477 : CALLS/CALLG
06D7 478
06D7 479 : INPUTS:
06D7 480
06D7 481 : EFN(AP) = number of the event flag to set when all of the requested
06D7 482 : data is valid.
06D7 483 : NODE(AP) = pointer to nodename descriptor
06D7 484 : CSIDADR(AP) = address of CSID source/destination
06D7 485 : ITMLST(AP) = address of a list of item descriptors of the form:
06D7 486
06D7 487 : +-----+
06D7 488 : | ITEM CODE ! BUF. LENGTH !
06D7 489 : +-----+
06D7 490 : | BUFFER ADDRESS
06D7 491 : +-----+
06D7 492 : | ADDRESS TO RETURN LENGTH
06D7 493 : +-----+
06D7 494
06D7 495 : IOSB(AP) = address of a quadword I/O status block to receive final
06D7 496 : status
06D7 497 : ASTADR(AP) = address of an AST routine to be called when all of the
06D7 498 : requested data has been supplied.
06D7 499 : ASTPRM(AP) = 32 bit ast parameter
06D7 500
06D7 501 : IMPLICIT INPUTS:
06D7 502
06D7 503 : none
06D7 504
06D7 505 : OUTPUTS:
06D7 506
06D7 507 : none
06D7 508
06D7 509 : IMPLICIT OUTPUTS:
06D7 510
06D7 511 : none
06D7 512
06D7 513 : ROUTINE VALUE:
06D7 514
06D7 515 : SS$_NORMAL -> normal completion
06D7 516 : SS$_EXASTLM -> AST quota exceeded
06D7 517 : SS$_ACCVIO -> ITMLST can not be read by the calling access mode,
06D7 518 : or the return buffer or return length word can not
06D7 519 : be written by the calling access mode
06D7 520 : SS$_BADPARAM -> an invalid item identifier was supplied
06D7 521
06D7 522 : SIDE EFFECTS:
```

```
06D7 523 :
06D7 524 : none
06D7 525 :--
06D7 526 :
00000000 527 .PSECT YEXEPAGED ; only entry mask in this program section
0000 528
06D2' 06D7 529 .ENTRY EXE$GETSYI,^M<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>
31 0002 530 BRW EXE_GETSYI ; transfer to real procedure
0005 531
000006D7 532 .PSECT YF$$$SYSGETSYI
06D7 533
06D7 534 :
06D7 535 : Allocate some local space on the stack
06D7 536
06D7 537 EXE_GETSYI:
5E E0 AE DE 06D7 538 MOVAL LOCAL_SPACE(SP), SP
FC AD D4 06DB 539 CLRL FLAG$ (FP) ; reset the flags longword
030D 30 06DE 540 BSBW NAMCSID ; process nodename/CSID pair
18 50 E9 06E1 541 BLBC R0,4$
06E4 542
06E4 543 :
06E4 544 : Check for and clear possible IOSB
06E4 545 :
51 14 AC D0 06E4 546 MOVL IOSB(AP),R1 ; get IOSB address
08 13 06E8 547 BEQL 3$ ; branch if none
06EA 548 IFNOWRT #8,(R1),30$ ; check write access to it
61 7C 06F0 549 CLRQ (R1) ; clear IOSB
06F2 550
06F2 551 : Check for and clear event flag
06F2 552 :
53 04 AC 9A 06F2 553 3$: MOVZBL EFN(AP),R3 ; get event flag number
00000000'GF 16 06F6 554 JSB G^SCH$CLREF ; clear event flag
6B 50 E9 06FC 555 4$: BLBC R0,GRET ; and return on errors
06FF 556 :
06FF 557 : Validate AST, if present
06FF 558 :
18 AC D5 06FF 559 TSTL ASTADR(AP)
OC 13 0702 560 BEQL 5$ ; no AST to check
54 00000000'GF D0 0704 561 MOVL G^CTL$GL_PCB,R4 ; get our PCB address
38 A4 B5 070B 562 TSTW PCB$W_ASTCNT(R4) ; is AST quota exceeded?
4B 15 070E 563 BLEQ 40$ ; branch if so and return error
0710 564 :
0710 565 : Loop through item descriptors, validating the requested item
0710 566 : identifiers and moving accessible items. A zero item identifier
0710 567 : terminates the list.
0710 568 :
55 10 AC D0 0710 569 5$: MOVL ITMLST(AP),R5 ; get item descriptor list address
4C 13 0714 570 BEQL 50$ ; ITMLST not optional
0716 571 IFNORD #4,(R5),30$ ; check first longword readable
071C 572 10$: ; top of item-get loop
56 85 3C 071C 573 MOVZWL (R5)+,R6 ; get buffer size
51 85 3C 071F 574 MOVZWL (R5)+,R1 ; get item identifier
43 13 0722 575 BEQL 60$ ; done if zero, take normal exit
0724 576 IFNORD #12,(R5),30$ ; check rest of this descriptor ...
072A 577 ; plus first longword of next one
57 85 7D 072A 578 MOVQ (R5)+,R7 ; R7 = buffer address, R8 = length address
51 DD 072D 579 PUSHL R1 ; save R1 across accessibility check
```



```
50 57 D0 072F 580      MOVL R7,R0      ; buffer address to R0
51 56 D0 0732 581      MOVL R6,R1      ; and size to R1
53 55 D4 0735 582      CLRL R3        ; PROBE will use PSL<PRVMOD>
00000000'EF 16 0737 583      JSB EX$PROBEW ; check write accessibility of buffer
16 50 E9 073D 584      BLBC R0,30$    ; buffer not accessible
51 8ED0 0740 585      POPL R1        ; restore R1 for use by CHECKITEM
55 55 DD 0743 586      PUSHL R5      ; save R5 across item check
0075 30 0745 587      BSBW CHECKITEM ; check item's validity
17 50 E9 0748 588      BLBC R0,50$    ; return error if not valid
00F8 30 074B 589      BSBW PUTDATA   ; put the item requested in user buffer
55 8ED0 074E 590      POPL R5        ; unsave R5
C8 50 E8 0751 591      BLBS R0,10$    ; continue on success
14 11 0754 592      BRB GRÉT
0756 593
0756 594
0756 595 ; Error/success dispatch points:
0756 596
50 0C 3C 0756 597 30$: MOVZWL #$$$_ACCVIO,R0 ; access violation
OF 11 0759 598      BRB GRÉT        ; terminate service below
50 2A04 8F 3C 075B 599 40$: MOVZWL #$$$_EXASTLM,R0 ; AST quota exceeded
08 11 0760 600      BRB GRÉT        ; terminate service below
50 14 3C 0762 601 50$: MOVZWL #$$$_BADPARAM,R0 ; illegal item or request
03 11 0765 602      BRB GRÉT        ; terminate service below
50 01 3C 0767 603 60$: MOVZWL #$$$_NORMAL,R0 ; normal return
076A 604
076A 605 ; Set the event flag, post completion status, and declare completion AST
076A 606
54 50 DD 076A 607 GRÉT: PUSHL R0      ; save completion status
00000000'GF 51 60 A4 D0 076C 608      MOVL G^CTL$GL PCB,R4 ; get PCB address
53 04 AC 9A 0773 609      MOVL PCB$$_PID(R4),R1 ; get process's PID
00000000'GF 51 14 AC D0 0777 610      CLRL R2        ; set null priority increment
53 04 AC 9A 0779 611      MOVZBL EFN(AP),R3 ; get event flag number to set
00000000'GF 51 14 AC D0 077D 612      JSB G^SCH$POSTEF ; set the event flag
51 09 13 0783 613 10$: MOVL IOSB(AP),R1 ; get address of IOSB
09 13 0787 614      BEQL 20$        ; branch if none
0789 615      IFNOWRT #8,(R1),20$ ; check if writable
55 61 6E D0 078F 616      MOVL (SP),(R1) ; store completion status
55 18 AC D0 0792 617 20$: MOVL ASTADR(AP),R5 ; get address of AST routine
15 13 0796 618      BEQL 30$        ; branch if none specified
54 54 02 16 DC 0798 619      MOVPSL R4 ; get PSL
54 54 02 16 EF 079A 620      EXTZV #PSL$V_PRVMOD,#PSL$$_PRVMOD,R4,R4 ; extract previous mode
50 8ED0 079F 621      $DCLAST S (R5),ASTPRM(AP),R4 ; queue the completion AST
04 07AD 622 30$: POPL R0 ; restore completion status
07B0 623      RET ; and return.
07B1 624
```

```

07B1 626      .SBTTL CHECKITEM - Validate item identifier
07B1 627
07B1 628      :++
07B1 629
07B1 630      : FUNCTIONAL DESCRIPTION:
07B1 631
07B1 632      :     Routine to validate item identifier and return information
07B1 633      :     about the item.
07B1 634
07B1 635      : CALLING SEQUENCE:
07B1 636
07B1 637      :     JSB/BSB
07B1 638
07B1 639      : INPUTS:
07B1 640
07B1 641      :     R1 = item identifier
07B1 642
07B1 643      : IMPLICIT INPUTS:
07B1 644
07B1 645      :     none
07B1 646
07B1 647      : OUTPUTS:
07B1 648
07B1 649      :     R1 = item identifier
07B1 650      :     R2 = structure number
07B1 651      :     R3 = item length
07B1 652      :     R4 = item source address
07B1 653      :     R5 = item type code
07B1 654      :     BITSIZ(FP) - if FLD
07B1 655      :     BITPOS(FP) - if FLD
07B1 656
07B1 657      : IMPLICIT OUTPUTS:
07B1 658
07B1 659      :     none
07B1 660
07B1 661      : ROUTINE VALUE:
07B1 662
07B1 663      :     R0 low bit set -> successful return
07B1 664      :     R0 low bit clear -> invalid item identifier
07B1 665
07B1 666      : SIDE EFFECTS:
07B1 667
07B1 668      :     none
07B1 669      :--

```



```
07B1 671 :
07B1 672 : This table is used to convert the pre V4 GETSYI item-codes to the
07B1 673 : new ones, which have a different form.
07B1 674 :
07B1 675 : Old form:
07B1 676 :      +-----+-----+
07B1 677 :      ; 8 bits ; 8 bits ;
07B1 678 :      +-----+-----+
07B1 678 :      SYIS_OLDVERSION =      01      00
07B1 679 :      SYIS_OLDCPU =      02      00
07B1 680 :      SYIS_OLDSID =      02      01
07B1 681 :
07B1 682 : New form:
07B1 683 :      +-----+-----+
07B1 684 :      ; 4 ; 12 bits ;
07B1 685 :      +-----+-----+
07B1 685 :      compatible with old = 0
07B1 686 :      EXE items = 1
07B1 687 :      FLD items = 2
07B1 688 :
07B1 689 :
07B1 690 COMPAT:
07B1 691      .WORD SYIS_OLDVERSION, SYIS_VERSION
07B5 692      .WORD SYIS_OLDCPU, SYIS_CPU
07B9 693      .WORD SYIS_OLDSID, SYIS_SID
07BD 694
07BD 695      .ENABLE LOCAL_BLOCK
07BD 696
07BD 697 CHECKITEM:
07BD 698      CLRL R0 ; assume error
07BF 699      BITW #^XF000, R1 ; is it a new item-code?
07C4 700      BNEQU 10$ ; NEQU means it is
07C6 701      MOVZBL #3, R3 ; setup to scan table
07C9 702      MOVAV COMPAT-2, R2
07CD 703 5$: TSTW (R2)+ ; skip past new item-code
07CF 704      CMPW (R2)+, R1 ; does it match this old item-codes?
07D2 705      BNEQU 7$ ; NEQU means it does not
07D4 706      MOVW (R2), R1 ; match, use the new itemcode instead
07D7 707      BRB 10$ ; continue like nothing happened
07D9 708 7$: SOBGTR R3, 5$ ; cycle through the table
07DC 709      BRB 900$ ; error if it wasn't in the table
07DE 710 10$: EXTZV #12, #4, R1, R2 ; get the structure number
07E3 711      EXTZV #0, #12, R1, R3 ; get the item number
07E8 712      CMPB R2, #MAXSTRUC ; is it a legal structure number?
07EB 713      BGTRU 900$ ; GTRU means it is not
07ED 714      CMPW R3, MAXCOUNT-2[R2] ; is it a legal item number?
07F3 715      BGTRU 900$ ; GTRU means it is not
07F5 716      CASE R2, <EXES$, FLD$>B, #1 ; goto the appropriate code
07FD 717
07FD 718 EXES$: MULL #5, R3 ; calc total offset
0800 719      MOVAB EXETBL[R3], R3 ; get address of table element
0806 720      BRB 50$
0808 721
0808 722 FLDS$: MULL #7, R3 ; calc total offset
080B 723      MOVAB FLDTBL[R3], R3 ; get address of table element
0811 724      EXTZV #11, #5, (R3), BITSIZ(FP) ; get (bitsiz-1) value
0817 725      INCL BITSIZ(FP) ; restore its original value
081A 726      EXTZV #0, #11, (R3), BITPOS(FP) ; get bitpos value
0820 727      TSTW (R3)+ ; point to next longword
```

```

55 63 03 05 EF 0827 731 50$: MOVL (R3)+, R4 ; get source address
53 63 05 00 EF 0827 732 ; NULL SOURCE MEANS RETIRED ITEM-CODE!!
53 63 05 50 D6 0827 733 ; IT ALSO MEANS PR$ KSP WILL NEVER BE
53 63 05 50 D6 0827 734 ; ABLE TO BE AN ITEM-CODE!
53 63 05 50 D6 0827 735 70$: EXTZV #5,#3,(R3),R5 ; get DTYPE
53 63 05 50 D6 0827 736 70$: EXTZV #0,#5,(R3),R3 ; get OUTLEN
53 63 05 50 D6 0827 737 70$: INCL R0 ; success!
53 63 05 50 D6 0827 738 900$: RSB ; return to caller
53 63 05 50 D6 0827 739 100$: BISL #<1@SYI_V_RETIRED>,FLAGS(FP) ; mark it as obsolete
53 63 05 50 D6 0827 740 100$: MOVL #4,R3 ; src length
53 63 05 50 D6 0827 741 100$: MOVAL SPECIAL_SPACE(FP),R4 ; scratch area
53 63 05 50 D6 0827 742 100$: CLRL (R4) ; null answer now
53 63 05 50 D6 0827 743 100$: MOVL #VALUE,R5 ; dtype
53 63 05 50 D6 0827 744 100$: BRB 70$ ; success exit
53 63 05 50 D6 0827 745 100$: .DISABLE LOCAL_BLOCK
53 63 05 50 D6 0827 746 100$:
```



```

0846 748      .SBTTL PUTDATA - Put requested data in user buffer
0846 749
0846 750      :++
0846 751
0846 752      : FUNCTIONAL DESCRIPTION:
0846 753
0846 754      :     This routine moves the requested data to the user's buffer and
0846 755      :     returns the actual data length to the user. It assumes that the
0846 756      :     user's buffer has been probed.
0846 757
0846 758      : CALLING SEQUENCE:
0846 759
0846 760      :     JSB/BSB
0846 761
0846 762      : INPUTS:
0846 763
0846 764      :     R1 = item identifier
0846 765      :     R2 = data structure number
0846 766      :     R3 = item length
0846 767      :     R4 = item address
0846 768      :     R5 = item type code
0846 769      :     R6 = user buffer length
0846 770      :     R7 = user buffer address
0846 771      :     R8 = address to return length
0846 772      :     BITSIZ(FP)
0846 773      :     BITPOS(FP)
0846 774
0846 775      : IMPLICIT INPUTS:
0846 776
0846 777      :     none
0846 778
0846 779      : OUTPUTS:
0846 780
0846 781      :     none
0846 782
0846 783      : IMPLICIT OUTPUTS:
0846 784
0846 785      :     none
0846 786
0846 787      : ROUTINE VALUE:
0846 788
0846 789      :     R0 low bit set -> success
0846 790      :     R0 low bit clear -> access violation on write of length
0846 791
0846 792      : SIDE EFFECTS:
0846 793
0846 794      :     Registers R1-R4 destroyed
0846 795      :--

```

```
0846 797
0846 798 PUTDATA:
0846 799
0846 800 :
0846 801 : Call routine to check for special conditions
0846 802 :
0846 803 :
0846 804 BBS #SYI_V_RETIRED,FLAGS(FP),15$ ; skip alot for oldie items
0846 805 BSBB CHECK_SPC ; handle special items
0846 806 BLBC R0,50$ ; were we successful?
0850 807
0850 808 :
0850 809 : Check for counted string, and find actual length if so.
0850 810 :
0850 811 :
0850 812 CMPL #CSTRING,R5 ; is this special string?
0853 813 BNEQ 10$ ; branch if not
0855 814 MOVZBL (R4)+,R3 ; get length and skip length byte
0858 815 :
0858 816 : Fetch the bitpos and bitsiz if it's a FLD item
0858 817 :
0858 818 10$: CMPL R2, #SYISC_FLDTYPE ; is it FLD?
0858 819 BNEQU 15$ ; NEQU means it is not
0858 820 MOVL BITSIZ(FP), R0 ; get bitsiz
0861 821 MOVL BITPOS(FP), R1 ; get bitpos
0865 822 MOVL (R4), TEMPORARY(FP) ; get copy of cell
0869 823 MOVAL TEMPORARY(FP), R4 ; point to copy
0869 824 EXTZV R1,R0,(R4),(R4) ; fetch sub-field and save
0872 825 :
0872 826 : Move the data
0872 827 :
0872 828 15$: PUSHR #*M<R3,R5> ; save needed registers from movc
0874 829 MOVCS R3,(R4),#0,R6,(R7) ; move data to user's buffer, zero fill
087A 830 POPR #*M<R3,R5> ; restore registers
087C 831 TSTL R8 ; did caller want return length?
087E 832 BEQL 30$ ; branch if not
0880 833 IFNOWRT #2,(R8),40$ ; exit if word not writable
0886 834 BBC #SYI_V_RETIRED,FLAGS(FP),18$ ;
0888 835 CLRL R3 ; make his retlen null
088D 836 18$: CMPL R3,R6 ; see how much was moved
0890 837 BLEQ 20$ ; use valid data length if it fit
0892 838 MOVL R6,R3 ; else give him "too short" buffer size
0895 839 20$: MOVW R3,(R8) ; return length to user
0898 840 :
0898 841 30$: MOVZWL #SS$_NORMAL,R0 ; set success code
089B 842 RSB
089C 843 :
089C 844 40$: MOVZWL #SS$_ACCVIO,R0 ; set error code
089F 845 50$: RSB ; return
```



```
08A0 847      .SBTTL SPECIAL - Handle special conditions
08A0 848
08A0 849      :++
08A0 850      :
08A0 851      : FUNCTIONAL DESCRIPTION:
08A0 852      :
08A0 853      :     These routines handle data items which must be transformed
08A0 854      :     before they are returned to the user. Generally, some
08A0 855      :     transformation is applied to the data item and the newly
08A0 856      :     computed item is stored in SPECIAL_SPACE on the stack.
08A0 857      :     The handling routine then changes R4 to point to SPECIAL_SPACE
08A0 858      :     so that PUTDATA will move the item from local storage.
08A0 859      :
08A0 860      : CALLING SEQUENCE:
08A0 861      :
08A0 862      :     JSB/BSB
08A0 863      :
08A0 864      : INPUTS:
08A0 865      :
08A0 866      :     R1 = item identifier
08A0 867      :     R3 = item length
08A0 868      :     R4 = item address/offset
08A0 869      :     R9 = target CSB address
08A0 870      :     R11 = target CSID
08A0 871      :
08A0 872      : IMPLICIT INPUTS:
08A0 873      :
08A0 874      :     none
08A0 875      :
08A0 876      : OUTPUTS:
08A0 877      :
08A0 878      :     none
08A0 879      :
08A0 880      : IMPLICIT OUTPUTS:
08A0 881      :
08A0 882      :     none
08A0 883      :
08A0 884      : ROUTINE VALUE:
08A0 885      :
08A0 886      :     none
08A0 887      :
08A0 888      : SIDE EFFECTS:
08A0 889      :
08A0 890      :     none
08A0 891      :--
```

EXE
FETC
FLAG
FLDS
FLDT
GETS
GETC
GOTO
GOTN
GRET
IOCS
IOCS
IOCS
IOCS
IOCS
IOCS
IOCS
IOCS
IOSB
IPLS
IPLS
ITML
LCKS
LCKS
LCKS
LCKS
LCKS
LCKS
LNMS
LNMS
LOCA
LOCA
LOCK
LOCK
MAXC
MAXS
MAXS
MAXS
MMGS
MMGS
MMGS
MMGS
MPWS
MPWS
MPWS
MPWS
MPWS
MPWS
MPWS
MPWS
NAMC
NODE
NODE
NONE
NULL
NULL
OUTL
PCBS
PCBS
PFLS
PFLS


```
08A0 893
08A0 894 CHECK_SPC:
08A0 895
08A0 896
08A0 897 : Registers R5 - R8 are saved at this level and may be used by
08A0 898 : the action routines without being saved. Action routines are JSB'ed
08A0 899 : to with R5 containing the address of SPECIAL_SPACE on the stack.
08A0 900
08A0 901
55 01E0 8F BB 08A0 902 PUSH R #^M<R5,R6,R7,R8> ; save registers
    EC AD DE 08A4 903 MOVAL SPECIAL_SPACE(FP),R5 ; local storage for action routine
    65 7C 08A8 904 CLRQ (R5) ; clear the special buffer
    08 A5 7C 08AA 905 CLRQ 8(R5)
    50 01 3C 08AD 906 MOVZWL #SS$ NORMAL,R0 ; assume success
    57 1A D0 08B0 907 MOVL #SPECIAL_LEN,R7 ; get number of table entries
58 FD84 CF DE 08B3 908 MOVAL SPECIAL,R8 ; get address of table
    88 51 B1 08B8 909 10$:
    13 13 08BB 910 CMPW R1,(R8)+ ; does entry match item?
    58 04 C0 08BD 911 BEQL 20$ ; yes, go handle it
    F5 57 F5 08BD 912 ADDL #4,R8 ; skip handler address
    03 FC AD 02 E1 08C0 913 SOBGTR R7,10$ ; scan rest of table
    54 55 D0 08C3 914
    01E0 8F BA 08C3 915 BBC #SYI V_REMOTE_NODE,FLAGS(FP),35$ ; nonlocal noncluster info?
    05 08C8 916 MOVL R5,R4 ; make the returned data null
    08CF 917 35$: POPR #^M<R5,R6,R7,R8> ; restore registers
    08D0 918 RSB
    08D0 919
    98 16 08D0 920 20$: JSB @ (R8)+ ; call action routine
    F7 11 08D2 921 BRB 35$
    08D4 922
    08D4 923
    08D4 924 : Data handling routines
    08D4 925 : *****
    08D4 926 : ALL NON-CLUSTER SPECIAL DATA ITEMS SHOULD TEST REMOTE_NODE AS BELOW
    08D4 927 : *****
    08D4 928
    08D4 929
    08D4 930
    08D4 931
    08D4 932 : Is the SCS code loaded?
    08D4 933
    08D4 934
    5C FC AD 02 E0 08D4 935 SPC_EXISTS:
    00000000 EF D5 08D4 936 BBS #SYI V_REMOTE_NODE,FLAGS(FP),POINT_R4 ; skip it for remotes
    54 13 08D9 937 TSTL SCS$GA_EXISTS ; is the cell empty?
    65 D6 08DF 938 BEQLU POINT_R4 ; null cell means it doesn't exist
    50 11 08E1 939 INCL (R5) ; make result TRUE
    08E3 940 BRB POINT_R4
    08E5 941
    08E5 942
    08E5 943 : Processor registers require special instructions to fetch
    08E5 944
    08E5 945
    4B FC AD 02 E0 08E5 946 SPC_PROCREG:
    65 54 DB 08E5 947 BBS #SYI V_REMOTE_NODE,FLAGS(FP),POINT_R4 ; skip it for remotes
    46 11 08EA 948 MFPR R4,(R5) ; get the register contents
    08ED 949 BRB POINT_R4
```


Line	Op	Op2	Op3	Op4	Op5	Op6	Op7	Op8	Op9	Op10	Op11	Op12	Op13	Op14	Op15	Op16	Op17	Op18	Op19	Op20	Op21	Op22	Op23	Op24	Op25	Op26	Op27	Op28	Op29	Op30	Op31	Op32	Op33	Op34	Op35	Op36	Op37	Op38	Op39	Op40	Op41	Op42	Op43	Op44	Op45	Op46	Op47	Op48	Op49	Op50	Op51	Op52	Op53	Op54	Op55	Op56	Op57	Op58	Op59	Op60	Op61	Op62	Op63	Op64	Op65	Op66	Op67	Op68	Op69	Op70	Op71	Op72	Op73	Op74	Op75	Op76	Op77	Op78	Op79	Op80	Op81	Op82	Op83	Op84	Op85	Op86	Op87	Op88	Op89	Op90	Op91	Op92	Op93	Op94	Op95	Op96	Op97	Op98	Op99	Op100	Op101	Op102	Op103	Op104	Op105	Op106	Op107	Op108	Op109	Op110	Op111	Op112	Op113	Op114	Op115	Op116	Op117	Op118	Op119	Op120	Op121	Op122	Op123	Op124	Op125	Op126	Op127	Op128	Op129	Op130	Op131	Op132	Op133	Op134	Op135	Op136	Op137	Op138	Op139	Op140	Op141	Op142	Op143	Op144	Op145	Op146	Op147	Op148	Op149	Op150	Op151	Op152	Op153	Op154	Op155	Op156	Op157	Op158	Op159	Op160	Op161	Op162	Op163	Op164	Op165	Op166	Op167	Op168	Op169	Op170	Op171	Op172	Op173	Op174	Op175	Op176	Op177	Op178	Op179	Op180	Op181	Op182	Op183	Op184	Op185	Op186	Op187	Op188	Op189	Op190	Op191	Op192	Op193	Op194	Op195	Op196	Op197	Op198	Op199	Op200	Op201	Op202	Op203	Op204	Op205	Op206	Op207	Op208	Op209	Op210	Op211	Op212	Op213	Op214	Op215	Op216	Op217	Op218	Op219	Op220	Op221	Op222	Op223	Op224	Op225	Op226	Op227	Op228	Op229	Op230	Op231	Op232	Op233	Op234	Op235	Op236	Op237	Op238	Op239	Op240	Op241	Op242	Op243	Op244	Op245	Op246	Op247	Op248	Op249	Op250	Op251	Op252	Op253	Op254	Op255	Op256	Op257	Op258	Op259	Op260	Op261	Op262	Op263	Op264	Op265	Op266	Op267	Op268	Op269	Op270	Op271	Op272	Op273	Op274	Op275	Op276	Op277	Op278	Op279	Op280	Op281	Op282	Op283	Op284	Op285	Op286	Op287	Op288	Op289	Op290	Op291	Op292	Op293	Op294	Op295	Op296	Op297	Op298	Op299	Op300	Op301	Op302	Op303	Op304	Op305	Op306	Op307	Op308	Op309	Op310	Op311	Op312	Op313	Op314	Op315	Op316	Op317	Op318	Op319	Op320	Op321	Op322	Op323	Op324	Op325	Op326	Op327	Op328	Op329	Op330	Op331	Op332	Op333	Op334	Op335	Op336	Op337	Op338	Op339	Op340	Op341	Op342	Op343	Op344	Op345	Op346	Op347	Op348	Op349	Op350	Op351	Op352	Op353	Op354	Op355	Op356	Op357	Op358	Op359	Op360	Op361	Op362	Op363	Op364	Op365	Op366	Op367	Op368	Op369	Op370	Op371	Op372	Op373	Op374	Op375	Op376	Op377	Op378	Op379	Op380	Op381	Op382	Op383	Op384	Op385	Op386	Op387	Op388	Op389	Op390	Op391	Op392	Op393	Op394	Op395	Op396	Op397	Op398	Op399	Op400	Op401	Op402	Op403	Op404	Op405	Op406	Op407	Op408	Op409	Op410	Op411	Op412	Op413	Op414	Op415	Op416	Op417	Op418	Op419	Op420	Op421	Op422	Op423	Op424	Op425	Op426	Op427	Op428	Op429	Op430	Op431	Op432	Op433	Op434	Op435	Op436	Op437	Op438	Op439	Op440	Op441	Op442	Op443	Op444	Op445	Op446	Op447	Op448	Op449	Op450	Op451	Op452	Op453	Op454	Op455	Op456	Op457	Op458	Op459	Op460	Op461	Op462	Op463	Op464	Op465	
------	----	-----	-----	-----	-----	-----	-----	-----	-----	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	--


```
0957 1007 FETCH_CLU:
        3F BB 0957 1008 PUSHR #*M<R0,R1,R2,R3,R4,R5> ; save the register past the MOVC3
65 64 53 28 0959 1009 MOVC3 R3,(R4),(R5) ; get the data into the special buffer
        3F BA 095D 1010 POPR #*M<R0,R1,R2,R3,R4,R5> ; restore the registers
        D1 11 095F 1011 SETIPL #0 ; drop IPL again
        0962 1012 BRB POINT_R4
        0964 1013
        0964 1014 VERIFY_CSB:
        0964 1015 CVTWL R11,R6 ; get the system index
56 00000000'FF 5B 32 0967 1016 MOVL @CLUSGL_CLUSVEC[R6],R6 ; get the CSB address
        0F 18 096F 1017 BGEQ 99$ ; GEQ means it is now unused
        59 56 D1 0971 1018 CMPL R6,R9 ; is it the same as ours?
        0A 12 0974 1019 BNEQ 99$ ; NEQ means it changed
        5B 4C A6 D1 0976 1020 CMPL CSB$$_CSID(R6),R11 ; is the CSID the same?
        04 12 097A 1021 BNEQ 99$ ; NEQ means it changed
        50 01 3C 097C 1022 MOVZWL #$$$_NORMAL,R0
        05 097F 1023 RSB
        0980 1024
        0980 1025 99$: SETIPL #0 ; drop IPL
        FC AD 02 CA 0983 1026 BICL2 #<1@SYI V INCLUSTER>,FLAGS(FP) ; reset the cluster flag
50 028C 8F 3C 0987 1027 MOVZWL #$$$_NOSUCHNODE,R0 ; declare an error
        05 098C 1028 RSB
        098D 1029
        098D 1030 LOCK:
        08 098D 1031 .BYTE IPL$ SCS
        098E 1032 ASSUME <.-SPC_LOCK> LE 512
        098E 1033
        098E 1034 ;
        098E 1035 ; Return total sizes for all page or swap files
        098E 1036 ;
        098E 1037 ; Input bit mask in R4
        098E 1038 ; bit 0
        098E 1039 ; 0 -> page file
        098E 1040 ; 1 -> swap file
        098E 1041 ; bit 1
        098E 1042 ; 0 -> total space
        098E 1043 ; 1 -> free space
        098E 1044 ; bit 2
        098E 1045 ; 1 -> keeps it from being null
        098E 1046
        098E 1047
        098E 1048 SPC_PAGESWAP:
        A2 FC AD 02 E0 098E 1049 BBS #SYI V_REMOTE_NODE,FLAGS(FP),POINT_R4 ; skip it for remotes
        10 54 E8 0993 1050 BLBS R4,10$ ; swap file
57 00000000'EF 3C 0996 1051 MOVZWL SGN$GW_SWPFILCT,R7 ; first page file slot
58 00000000'EF D0 099D 1052 MOVL MMG$GL_MAXPFIDX,R8 ; last one
        0C 11 09A4 1053 BRB 20$ ; resume in common code
        09A6 1054
        57 01 D0 09A6 1055 10$: MOVL #1,R7 ; always the first swap file slot
58 00000000'EF 3C 09A9 1056 MOVZWL SGN$GW_SWPFILCT,R8
        58 D7 09B0 1057 DECL R8 ; max index for swap files
        09B2 1058
        20$: 09B2 1059 CLRL (R5) ; initial count
        58 57 C2 09B4 1060 SUHL R7,R8 ; slots to count - 1
        32 19 09B7 1061 BLSS 60$ ; none
57 00000000'FF 47 DE 09B9 1062 MOVAL @MMG$GL_PAGSWPVC[R7],R7 ; first slot
        56 87 D0 09C1 1063 30$: MOVL (R7)+,R8 ; address of PFL structure
```



```

- GET SYSTEM INFORMATION SYSTEM SERVICE 16-SEP-1984 02:10:18 VAX/VMS Macro V04-00
SPECIAL - Handle special conditions 5-SEP-1984 03:54:07 [SYS.SRC]SYSGETSYI.MAR:1

```

Page 24
(4)

Address	Hex	Asm	Comment
00000000	E7 56 D1	09C4 1064	CMP R6,MMG\$G_L_NULLPFL ; is it in use
	13 13	09CB 1065	BEQ 50\$; no
0E 23	A6 00 E1	09CD 1066	BBC #PFL\$V_INITED,PFL\$B_FLAGS(R6),50\$; not initd
06 54	01 E0	09D2 1067	BBS #1,R4,20\$; count free space
65 14	A6 C0	09D6 1068	ADDL PFL\$L_BITMAPSZ(R6),(R5) ; total size / 8
	04 11	09DA 1069	BRB 50\$
65 18	A6 C0	09DC 1070	ADDL PFL\$L_FREPAGECNT(R6),(R5) ; total free pages
	DE 58 F4	09E0 1071	SOBGEQ R8,30\$; loop over all files
		09E3 1072	;
04 54	01 E0	09E3 1073	BBS #1,R4,60\$; free space - already page count
65 65	03 78	09E7 1074	ASHL #3,(R5),(R5) ; convert byte count to page count
	FF47 31	09EB 1075	BRW POINT_R4 ; join common exit code
		09EE 1076	

[illegible]

```
09EE 1078 .SBTTL NAMCSID - Get specified node CSID
09EE 1079 :++
09EE 1080 :
09EE 1081 : FUNCTIONAL DESCRIPTION:
09EE 1082 :
09EE 1083 : Routine to convert a node name to a CSID. If a
09EE 1084 : valid CSID or node name is specified, the standard conversion
09EE 1085 : routine EXE$NAMCSID is simply called. If, however, a CSID that implies
09EE 1086 : a "wildcard" CSID (-1) is specified, then the next active node is
09EE 1087 : chosen as the node CSID to pass to EXE$NAMCSID. EXE$NAMCSID then
09EE 1088 : returns the node's CSB address.
09EE 1089 :
09EE 1090 : INPUTS:
09EE 1091 :
09EE 1092 : CSIDADR(AP) = address of specified CSID
09EE 1093 : NODE(AP) = address of specified process name descriptor
09EE 1094 :
09EE 1095 : OUTPUTS:
09EE 1096 :
09EE 1097 : R0 = success/failure of operation
09EE 1098 : R4 = current process PCB address
09EE 1099 : R9 = specified node CSB address
09EE 1100 : R11 = specified node CSID
09EE 1101 : @CSIDADR(AP) = specified node CSID or special "wildcard" context CSID
09EE 1102 :--
09EE 1103 :
00000008 09EE 1104 CSIDADR = 8
0000000C 09EE 1105 NODE = 12
09EE 1106 :
09EE 1107 NAMCSID:
09EE 1108 .ENABLE LOCAL_BLOCK
09EE 1109 :
09EE 1110 : MAKE SURE WE'RE IN A CLUSTER HERE
09EE 1111 :
09EE 1112 :
56 00000000'EF D0 09EE 1113 MOVL CLU$GL_CLUSTER,R6 ; GET CLUB ADDRESS
09EE 1114 BEQL 1$ ; IF EQL, NOT IN CLUSTER
04 1C A6 00 E1 09EE 1115 BBC #CLU$V_CLUSTER,CLU$CL_FLAGS(R6),1$ ; IF CLEAR, NOT A CLUSTER
FC AD 02 C8 09EE 1116 BISL2 #<1@SYI_V_INCLUSTER>,FLAGS(FP) ; mark that we're in a cluster
09EE 1117 :
56 08 AC D0 09EE 1118 1$: MOVL CSIDADR(AP),R6 ; get CSID address
4D 13 0A04 1119 BEQL 19$ ; if eql - none
09EE 1120 IFWRT #4,(R6),2$ ; check access to CSID
00CE 31 0A0C 1121 BRW 50$
50 66 D0 0A0F 1122 2$: MOVL (R6),R0 ; get CSID
3F 13 0A12 1123 BEQL 19$ ; if eql - none
79 14 0A14 1124 BGTR 20$ ; if gtr - standard CSID
09EE 1125 :
0A16 1126 : "Wildcard" type CSID specified
0A16 1127 :
0A16 1128 :
03 FC AD 01 E0 0A16 1129 BBS #SYI_V_INCLUSTER,FLAGS(FP),5$ ; are we in a cluster?
00C4 31 0A1B 1130 BRW 60$ ; wildcarding without a cluster!
09EE 1131 5$: SETIPL 80$ ; lock the cluster database
55 50 32 0A25 1132 CVTWL R0,R5 ; get NIX (Node Index) from CSID
FC AD 01 C8 0A28 1133 BISL2 #<1@SYI_V_WILD>,FLAGS(FP) ; mark wildcarding in effect
55 B6 0A2C 1134 10$: INCW R5 ; increment NIX
```



```

00000000'EF 55 B1 0A2E 1135 CMPW R5,CLUS$GW_MAXINDEX ; is NIX in valid range?
03 1F 0A35 1136 BLSSU 11$ ; if LSSU, yep
00A8 31 0A37 1137 BRW 60$ ; no more nodes
55 55 3C 0A3A 1138 11$: MOVZWL R5,R5 ; clear out the top half of R5
50 00000000'FF45 D0 0A3D 1139 MOVL @CLUS$GL_CLUSVEC[R5],R0 ; get CSB address
E5 18 0A45 1140 BGEQ 10$ ; if GEQ, unused - try next one
7E 4C A0 D0 0A47 1141 MOVL CSB$CL_CSID(R0),-(SP) ; get the CSID
66 8E D0 0A4B 1142 SETIPL #0 ; lower IPL to touch the argument list
3C 11 0A4E 1143 MOVL (SP)+,(R6) ; store CSID in argument list
0A51 1144 BRB 20$
0A53 1145
0A53 1146
0A53 1147
0A53 1148
0A53 1149 19$: BBS #SYI_V_INCLUSTER,FLAGS(FP),21$ ; let EXE$NAMCSID do it
3C FC AD 01 E0 0A53 1149 MOVL NODE(AP),R3 ; get the nodename argument
53 0C AC D0 0A58 1150 BEQL 75$ ; it was defaulted too, skip everything
71 13 0A5C 1151
0A5E 1152
0A5E 1153
0A5E 1154
0A5E 1155
0A5E 1156
0A5E 1157
52 63 7D 0A64 1158 IFNORD #8,(R3),50$ ; probe the descriptor
52 52 3C 0A67 1159 MOVQ (R3),R2 ; get the nodename descriptor
7D 13 0A6A 1160 MOVZWL R2,R2 ; is the length legal?
52 0F B1 0A6C 1161 BEQL 65$ ; EQL means nope
78 1F 0A6F 1162 CMPW #15,R2 ; is it too long?
0A71 1163 BLSSU 65$ ; LSSU means too long
51 00000000'GF DE 0A77 1164 IFNORD R2,(R3),50$ ; probe the string
55 44 A1 9E 0A7E 1165 MOVAL G^SCS$GA_LOCALSB,R1 ; point at the local SB
85 52 91 0A82 1166 MOVAB SB$T_NODENAME(R1),R5 ; get address of nodename
62 12 0A85 1167 CMPB R2,(R5)+ ; is it the right length?
65 63 52 29 0A87 1168 BNEQ 65$ ; NEQ means no
5C 12 0A8B 1169 CMPC3 R2,(R3),(R5) ; is it the same nodename?
40 11 0A8D 1170 BNEQ 65$ ; NEQ means this is NOT the one
0A8F 1171 BRB 75$ ; It is the local nodename, exit
0A8F 1172
0A8F 1173 ; Convert node name to CSID, if specified
0A8F 1174
4E FC AD 01 E1 0A8F 1175 20$: BBC #SYI_V_INCLUSTER,FLAGS(FP),60$ ; specified CSID - no cluster!
5C 04 C0 0A94 1176 21$: ADDL #4,AP ; make CSIDADR top argument
00000000'EF 16 0A97 1177 JSB 25$ ; get into nonpaged code
0A9D 1178 .SAVE_PSECT ; save current .PSECT context
0A9D 1179
0A9D 1180 ; The reason for jumping to the nonpaged exec rather than dynamically
0A9D 1181 ; locking down pageable pages is that EXE$NAMCSID cannot be entered
0A9D 1182 ; above IPL 2 and the dynamic locking would cause that to happen. The
0A9D 1183 ; reason that EXE$NAMCSID must be entered at IPL 2 or lower is that it
0A9D 1184 ; touches the caller's argument list (which contains arguments that
0A9D 1185 ; could fault) and page faults are not allowed above IPL 2.
0A9D 1186
0000AF1'EF 00000000 1187 .PSECT AEXENONPAGED ; EXE$NAMCSID returns at IPL$_SYNCH
16 0000 1188 JSB EXE$NAMCSID ; get CSB address and CSID
0006 1189 SETIPL #0 ; restore IPL - CSB is no longer locked
05 0009 1190 RSB ; go back to paged code
000A 1191

```

```

00000A9D 1192 .RESTORE PSECT ; get paged .PSECT context back
C2 0A9D 1193 SUBL #4,AP ; restore argument pointer
D0 0AA0 1194 MOVL R1,R11 ; save CSID
07 FC AD 00 E1 0AA3 1195 BBC #SYI V WILD,FLAGS(FP),30$ ; 'wildcard' type CSID specified?
66 51 B0 0AA8 1196 MOVW R1,(R6) ; restore node index context
02 A6 01 AE 0AAB 1197 MNEGW #1,2(R6) ; set continuation context
0AAF 1198 ;
0AAF 1199 ; Check CSID address and return
0AAF 1200 ;
20 50 E9 0AAF 1201 30$: BLBC R0,40$ ; branch if error
59 54 D0 0AB2 1202 MOVL R4,R9 ; save CSB address
54 00000000 EF D0 0AB5 1203 MOVL CLUSGL_CLUB,R4 ; get address of Cluster Block
04 12 0ABC 1204 BNEQU 32$ ; NEQU means it's not null
0ABE 1205 BUG CHECK ICONCLUDAT,FATAL ; oh oh
54 10 A4 DE 0AC2 1206 32$: MOVW CLUSL_LOCAL_CSB(R4),R4 ; get address of local CSB
59 64 D1 0AC6 1207 CMPL (R4),R9 ; see if local csb = target csb
04 13 0AC9 1208 BEQL 75$ ; EQL means target = local
FC AD 04 C8 0ACB 1209 BISL2 #<1>SYI V REMOTE_NODE>,FLAGS(FP) ; set the remote target flag
54 50 01 3C 0ACF 1210 75$: MOVZWL #SS$ NORMAL,R0 ; set success
00000000 EF D0 0AD2 1211 40$: MOVL SCH$GL_CURPCB,R4 ; restore current PCB address
0AD9 1212 SETIPL #0 ; make sure we can page fault
05 0ADC 1213 RSB
0ADD 1214
50 0C 3C 0ADD 1215 50$: MOVZWL #SS$_ACCVIO,R0 ; set access violation
F0 11 0AE0 1216 BRB 40$
50 0A00 8F 3C 0AE2 1217 60$: MOVZWL #SS$_NOMORENODE,R0 ; set no more nodes
E9 11 0AE7 1218 BRB 40$
50 028C 8F 3C 0AE9 1219 65$: MOVZWL #SS$_NOSUCHNODE,R0 ; set no such node
E2 11 0AEE 1220 BRB 40$
0AF0 1221
08 0AF0 1222 80$: .BYTE IPL$ SCS ; to lock the cluster database
0AF1 1223 ASSUME <.-5$> LE 512
0AF1 1224
0AF1 1225 .DISABLE LOCAL_BLOCK

```



```
OAF1 1227 .SBTTL EXES$NAMCSID - CONVERT NODE NAME TO CSID
OAF1 1228 :++
OAF1 1229 : EXES$NAMCSID - CONVERT NODE NAME TO CSID
OAF1 1230 :
OAF1 1231 : FUNCTIONAL DESCRIPTION:
OAF1 1232 : EXES$NAMCSID OBTAINS THE PROPER CSID AND CSB ADDRESS FOR A
OAF1 1233 : STANDARD NODE SERVICE ARGUMENT LIST CONSISTING
OAF1 1234 : OF A CSID/NODE-NAME PAIR. THE ABSENCE OF BOTH SELECTS THE
OAF1 1235 : CURRENT NODE.
OAF1 1236 :
OAF1 1237 : NOTE THAT THE OPERATION OF THIS ROUTINE ONLY MAKES SENSE IN
OAF1 1238 : A CLUSTER, THEREFORE A NOSUCHNODE ERROR WILL BE RETURNED IF
OAF1 1239 : CLU$GL_CLUB = 0 ON ENTRY.
OAF1 1240 :
OAF1 1241 : CALLING SEQUENCE:
OAF1 1242 : JSB/BSB EXES$NAMCSID
OAF1 1243 :
OAF1 1244 : INPUT PARAMETERS:
OAF1 1245 : CSID(AP) - ADDRESS OF CSID SOURCE/DESTINATION (CSID)
OAF1 1246 : NODENAME(AP) - POINTER TO NODE DESCRIPTOR TO CONVERT TO CSID
OAF1 1247 :
OAF1 1248 : IMPLICIT INPUTS:
OAF1 1249 : @CLU$GL_CLUSVEC - VECTOR OF CSB ADDRESSES
OAF1 1250 :
OAF1 1251 : OUTPUT PARAMETERS:
OAF1 1252 : R0 - COMPLETION STATUS
OAF1 1253 : R1 - NODE IDENTIFICATION (CSID) OF NAMED NODE.
OAF1 1254 : R4 - CSB ADDRESS OF NODE IF MATCH IS FOUND.
OAF1 1255 : @CSID(AP) - NODE IDENTIFICATION (CSID) OF SELECTED NODE
OAF1 1256 : IPL - IPL$_SYNCH (IPL UNCHANGED IF SSS$_ACCVIO OR SSS$_IVLOGNAM)
OAF1 1257 :
OAF1 1258 : COMPLETION CODES:
OAF1 1259 : SSS$_NORMAL - NORMAL SUCCESSFUL COMPLETION
OAF1 1260 : SSS$_IVLOGNAM - INVALID LOGICAL NAME STRING
OAF1 1261 : SSS$_NOSUCHNODE - NONEXISTENT NODE OR INVALID CSID
OAF1 1262 : SSS$_ACCVIO - ACCESS VIOLATION FOR WRITE DESTINATION
OAF1 1263 :
OAF1 1264 : SIDE EFFECTS:
OAF1 1265 : NONE
OAF1 1266 : --
OAF1 1267 :
00000004 OAF1 1268 CSID = 4 ; special offset for EXES$NAMCSID
00000008 OAF1 1269 NODENAME = 8 ; special offset for EXES$NAMCSID
OAF1 1270 :
OAF1 1271 EXES$NAMCSID: ; TRANSLATE PNAME TO CSID
OAF1 1272 .ENABLE LOCAL BLOCK
OAF1 1273 MFPR S^#PR$ IPL,R0 ; CHECK THE CURRENT IPL LEVEL
OAF1 1274 CMPL #IPL$_ASTDEL,R0 ; ARE WE ABOVE PAGE FAULT IPL?
OAF1 1275 BGEQU 8$ ; GOOD, WE CAN FAULT
OAF1 1276 BSBW 999$ ; CANNOT BE CALLED ABOVE ASTDEL
OAF1 1277 8$: MOVL CLU$GL_CLUB,R4 ; GET THE CLUSTER BLOCK ADDRESS
OAF1 1278 BNEQU 10$ ; GOOD, WE'RE IN A CLUSTER
OAF1 1279 BRW NONEX ; CANNOT BE CALLED IF NOT IN A CLUSTER
OAF1 1280 10$: MOVL CLUB$ LOCAL_CSB(R4),R4 ; GET THE CSB ADDRESS
OAF1 1281 MOVL CSID(AP),R0 ; GET CSID ADDRESS
OAF1 1282 BEQL 30$ ; NO CSID ADDRESS
OAF1 1283 IFWRT #4,(R0),20$ ; ERROR IF ACCESS VIOLATION
```

54 00000000 50 12 DB 50 02 D1 03 1E 00B5 30 0AF7 1275 00A3 31 0B05 1279 54 10 A4 DO 0B08 1280 50 04 AC DO 0B0C 1281 1A 13 0B10 1282 0B12 1283

```

50 0C 3C 0B18 1284 35$: MOVZWL #SS$_ACCVIO,R0 ; SET ACCESS VIOLATION ERROR CODE
                                05 0B1B 1285 RSB ; AND EXIT
51 60 D0 0B1C 1286 20$: MOVL (R0),R1 ; NOW FETCH CSID
                                0B 13 0B1F 1287 BEQL 30$ ; BRANCH IF NO CSID FOUND
                                50 D4 0B21 1288 CLRL R0 ; CLEAR CSID ADDRESS,
                                009F 31 0B23 1289 ; DON'T NEED TO REWRITE SAME VALUE
                                0B23 1290 BRW GOTCSID ; HAVE THE CSID, GO CHECK IT OUT
                                0B26 1291
50 0154 8F 3C 0B26 1292 45$: MOVZWL #SS$_IVLOGNAM,R0 ; BAD NODENAME STRING
                                05 0B2B 1293 RSB
                                0B2C 1294
                                0B2C 1295 ; NO CSID SPECIFIED (CSIDADR = 0 OR CSIDADR -> 0)
                                0B2C 1296
                                0B2C 1297 R4 -> LOCAL CSB
                                0B2C 1298 R0 = 0 OR R0 -> 0 (CSIDADR = 0 OR CSIDADR -> 0)
                                0B2C 1299 <R1,R2,R3> NOT INTERESTING
                                0B2C 1300
51 4C A4 D0 0B2C 1301 30$: MOVL CSB$_CSID(R4),R1 ; ASSUME LOCAL CSID
53 08 AC D0 0B30 1302 MOVL NODENAME(AP),R3 ; GET NODENAME ADDRESS IF SPECIFIED
                                03 12 0B34 1303 BNEQ 31$ ; NEQ MEANS NAME WAS SPECIFIED
                                008C 31 0B36 1304 BRW GOTCSID ; NO NAME SPECIFIED, USE CALLER'S CSID
                                0B39 1305 31$:
                                0B39 1306
                                0B39 1307 ; MUST LOOK UP NODE NAME. PROBE THE DESCRIPTOR AND THE STRING, AND THEN
                                0B39 1308 ; COPY IT TO THE STACK SO THAT IT CAN BE ACCESSED AFTER WE RAISE IPL.
                                0B39 1309
                                0B39 1310 R4 -> CURRENT CSB
                                0B39 1311 R3 -> NODE NAME DESCRIPTOR (ACCESS NOT YET PROBED)
                                0B39 1312 R0 = 0 OR R0 -> 0 (CSIDADR = 0 OR CSIDADR -> 0)
                                0B39 1313 <R1,R2> NOT INTERESTING
                                0B39 1314
                                0B39 1315 IFNORD #8,(R3),35$ ; PROBE THE DESCRIPTOR
52 63 7D 0B3F 1316 MOVQ (R3),R2 ; GET THE NODENAME DESCRIPTOR
52 52 3C 0B42 1317 MOVZWL R2,R2 ; IS THE LENGTH LEGAL?
                                DF 13 0B45 1318 BEQL 45$ ; EQL MEANS NOPE
52 0F B1 0B47 1319 CMPW #15,R2 ; IS IT TOO LONG?
                                DA 1F 0B4A 1320 BLSSU 45$ ; LSSU MEANS TOO LONG
                                0B4C 1321 IFNORD R2,(R3),35$ ; PROBE THE STRING
5E 10 C2 0B52 1322 SUBL #16,SP ; ALLOCATE BUFFER ON THE STACK
51 5E D0 0B55 1323 MOVL SP,R1 ; TEMPORARY POINTER TO BUFFER
                                52 DD 0B58 1324 PUSHL R2 ; SAVE LENGTH OF NODE NAME STRING
81 83 90 0B5A 1325 40$: MOVB (R3)+,(R1)+ ; COPY NODE NAME STRING FROM USER'S
FA 52 F5 0B5D 1326 SOBGTR R2,40$ ; BUFFER ONTO THE STACK
                                52 8ED0 0B60 1327 POPL R2 ; RESTORE LENGTH OF NODE NAME STRING
53 5E D0 0B63 1328 MOVL SP,R3 ; POINTER TO NODE NAME BUFFER
                                50 DD 0B66 1329 PUSHL R0 ; SAVE THE CSIDADR ARGUMENT
50 00000000'EF 3C 0B68 1330 MOVZWL CLUS$_MAXINDEX,R0 ; GET THE NUMBER OF ENTRIES
                                50 D7 0B6F 1331 DECL R0 ; CONVERT TO HIGHEST OFFSET
                                0B71 1332
                                0B71 1333 ; SCAN CSB VECTOR TO LOOK FOR THIS NODE NAME
                                0B71 1334
                                0B71 1335 R4 -> CURRENT CSB
                                0B71 1336 R3 -> USER'S NODE NAME STRING (IN BUFFER ON THE STACK)
                                0B71 1337 R2 = USER'S NODE NAME LENGTH
                                0B71 1338 R0 = COUNTER FOR CLUSVEC SLOTS
                                0B71 1339
0B71 1340 100$: SETIPL LOCKPAGE ; LOCK DOWN THE REST OF THE ROUTINE

```



```

51 00000000'FF40 D0 0B78 1341      MOVL    @CLUS$GL_CLUSVEC[R0],R1 ; GET THE POINTER TO THE CSB
      21 18 0B80 1342      BGEQ     155$ ; GEQ MEANS UNUSED, TRY THE NEXT ONE
      51 DD 0B82 1343      PUSHL    R1 ; SAVE THE POINTER TO THE TARGET CSB
      51 68 A1 D0 0B84 1344      MOVL    CSB$L_SB(R1),R1 ; GET SB ADDRESS
      0B88 1345
      0B88 1346 ; IS THIS THE NODENAME?
      0B88 1347 :
      0B88 1348 :
      0B88 1349 :
      0B88 1350 :
      0B88 1351 :
      0B88 1352 :
      55 DD 0B88 1353      PUSHL    R5 ; SAVE R5
      55 44 A1 9E 0B8A 1354      MOVAB    SB$T_NODENAME(R1),R5 ; GET ADDRESS OF NODENAME
      85 52 91 0B8E 1355      CMPB     R2,(R5)+ ; IS IT THE RIGHT LENGTH?
      0A 12 0B91 1356      BNEQ     150$ ; NEQ MEANS NO, TRY THE NEXT ONE
      0F BB 0B93 1357      PUSHR     #^M<R0,R1,R2,R3> ; SAVE REGISTERS FOR THE CMPC3
      65 63 52 29 0B95 1358      CMPC3    R2,(R3),(R5) ; IS IT THE SAME NODENAME?
      0F BA 0B99 1359      POPR      #^M<R0,R1,R2,R3> ; RESTORE REGISTERS
      18 13 0B9B 1360      BEQL     GOTNAM ; EQL MEANS THIS IS THE ONE
      0B9D 1361
      0B9D 1362 ; DID NOT FIND THE NODE BY NAME
      0B9D 1363
      55 8ED0 0B9D 1364 150$: POPL     R5 ; RESTORE R5
      51 8ED0 0BA0 1365      POPL     R1 ; RESTORE TARGET CSB ADDRESS
      CB 50 F4 0BA3 1366 155$: SOBGEQ  R0,100$ ; LOOP IF NOT DONE
      8E D5 0BA6 1367      TSTL     (SP)+ ; THROW AWAY R0 FROM STACK
      5E 10 C0 0BAB 1368      ADDL     #16,SP ; POP NODE NAME BUFFER FROM STACK
      0BAB 1369
      0BAB 1370 ; EXIT WITH NONEXISTENT NODE STATUS
      0BAB 1371
      50 028C 8F 3C 0BAB 1372 NONEX: MOVZWL #SS$_NOSUCHNODE,R0 ; SET ERROR STATUS
      05 0B80 1373      RSB ; AND RETURN TO CALLER
      0B81 1374
      0B81 1375 ; EXIT WITH A CRASH DUMP
      0B81 1376
      0B81 1377 999$: BUG_CHECK ICONCLUDAT,FATAL
      0B85 1378
      0B85 1379 ; FOUND THE NODE NAME, GET CSID FROM CSB AND CLEAN OFF THE STACK
      0B85 1380 :
      0B85 1381 :
      0B85 1382 :
      0B85 1383 GOTNAM: POPL     R5 ; RESTORE R5
      51 8ED0 0B88 1384      POPL     R1 ; RESTORE TARGET CSB ADDRESS
      4C A1 D0 0B8B 1385      MOVL     CSB$L_CSID(R1),R1 ; GET FULL CSID FOR NAME
      50 8ED0 0B8F 1386      POPL     R0 ; RESTORE CSIDADR ARGUMENT
      5E 10 C0 0BC2 1387      ADDL     #16,SP ; POP NODE NAME BUFFER FROM STACK
      0BC5 1388
      0BC5 1389 ; FOUND THE TARGET CSID, VERIFY IT
      0BC5 1390 :
      0BC5 1391 :
      0BC5 1392 :
      0BC5 1393 :
      0BC5 1394 :
      0BC5 1395 :
      0BC5 1396 GOTCSID:
      0BC5 1397      SETIPL  LOCKPAGE ; BLOCK SYSTEM EVENTS

```

```

52 00000000'EF 51 3C OBCC 1398 MOVZWL R1,R2 ; EXTRACT NODE INDEX
52 00000000'FF 52 B1 OBCF 1399 CMPW R2,CLUS$GW_MAXINDEX ; TEST AGAINST MAXIMUM VALUE
52 00000000'FF 53 1E OBD6 1400 BGEQU NONEX ; NONEXISTENT IF GEQU THAN MAXINDEX
4C A2 51 3C OBD8 1401 MOVL @CLUS$GL_CLUSVEC[R2],R2 ; GET CSB ADDRESS
51 18 OBE0 1402 BGEQ NONEX ; GEQ MEANS IT'S UNUSED
51 51 D1 OBE2 1403 CMPL R1,CSB$L_CSID(R2) ; CHECK FOR VALID CSID
51 51 C3 12 OBE6 1404 BNEQ NONEX ; NOT THE SAME
51 51 C3 12 OBE8 1405
51 51 C3 12 OBE8 1406 RETURN: ; SUCCESSFUL EXIT
54 52 D0 OBE8 1407 MOVL R2,R4 ; MOVE CSB ADDRESS OF TARGET
54 52 D0 OBE8 1408 ; NORMAL STATUS EXIT
54 52 D0 OBE8 1409 TSTL R0 ; WAS CSID ADDRESS SPECIFIED
54 52 D0 OBE8 1410 BEQL 910$ ; NO, SKIP STORE OF CSID
54 52 D0 OBE8 1411 SETIPL #IPL$ ASTDEL ; ALLOW PAGE FAULTS
54 52 D0 OBE8 1412 MOVL R1,(R0) ; STORE CSID IN DESTINATION
54 52 D0 OBE8 1413 CLRL R0 ; DO NOT WRITE CSID A SECOND TIME
54 52 D0 OBE8 1414 BRB GOTCSID ; MAKE SURE THAT CSID IS STILL VALID
54 52 D0 OBE8 1415
54 52 D0 OBE8 1416 910$: MOVZWL #SS$_NORMAL,R0 ; SET SUCCESS STATUS
54 52 D0 OBE8 1417 RSB ; AND RETURN TO CALLER
54 52 D0 OBE8 1418
54 52 D0 OBE8 1419 ; LOCK THIS PAGE DOWN WHEN WE RAISE IPL
54 52 D0 OBE8 1420 ;
54 52 D0 OBE8 1421
54 52 D0 OBE8 1422 LOCKPAGE:
54 52 D0 OBE8 1423 .BYTE IPL$ SCS ; END OF LOCKED CODE REGION
54 52 D0 OBE8 1424 ASSUME <.-100$> LE 512
54 52 D0 OBE8 1425
54 52 D0 OBE8 1426 .DISABLE LOCAL_BLOCK
54 52 D0 OBE8 1427
54 52 D0 OBE8 1428 .END
```


SYSGETSYI
Symbol table

N 9
- GET SYSTEM INFORMATION SYSTEM SERVICE 16-SEP-1984 02:10:18 VAX/VMS Macro V04-00
5-SEP-1984 03:54:07 [SYS.SRC]SYSGETSYI.MAR;1

Page 32
(6)

```

$ST1 = 00000000
ACPSGB_BASEPRIO ***** X 02
ACPSGB_DATACHK ***** X 02
ACPSGB_MAXREAD ***** X 02
ACPSGB_SWAPFLGS ***** X 02
ACPSGB_WINDOW ***** X 02
ACPSGB_WRITBACK ***** X 02
ACPSGW_DINDXCACHE ***** X 02
ACPSGW_DIRCACHE ***** X 02
ACPSGW_EXTCACHE ***** X 02
ACPSGW_EXTLIMIT ***** X 02
ACPSGW_FIDCACHE ***** X 02
ACPSGW_HDRCACHE ***** X 02
ACPSGW_MAPCACHE ***** X 02
ACPSGW_QUOCACHE ***** X 02
ACPSGW_SYSACC ***** X 02
ACPSGW_WORKSET ***** X 02
ACPSV_READCHK = 00000000 G
ACPSV_SWAPGRP = 00000001 G
ACPSV_SWAPMAG = 00000003 G
ACPSV_SWAPPRV = 00000002 G
ACPSV_SWAPSYS = 00000000 G
ACPSV_WRITECHK = 00000001 G
ARCSV_CHAR_EMUL = 00000004
ARCSV_DCML_EMUL = 00000005
ARCSV_DFLT_EMUL = 00000008
ARCSV_FFLT_EMUL = 00000009
ARCSV_GFLT_EMUL = 0000000A
ARCSV_HFLT_EMUL = 0000000B
ASTADR = 00000018
ASTPRM = 0000001C
BIT... = 00000001
BITPOS = FFFFFFFE4
BITSIZ = FFFFFFFE0
BSTRING = 00000001
BUG$ ICONCLUDAT ***** X 02
CHECKITEM 000007BD R 02
CHECK_SPC 000008A0 R 02
CLUSGB_QDISK ***** X 02
CLUSGB_VAXCLUSTER ***** X 02
CLUSGL_ALLOCLS ***** X 02
CLUSGL_CLUB ***** X 02
CLUSGL_CLUSVEC ***** X 02
CLUSGW_LCKDIRWT ***** X 02
CLUSGW_MAXINDEX ***** X 02
CLUSGW_QDSKINTERVAL ***** X 02
CLUSGW_QDSKVOTES ***** X 02
CLUSGW_QUORUM ***** X 02
CLUSGW_RECINT ***** X 02
CLUSGW_VOTES ***** X 02
CLUB$B_FSYSID = 00000026
CLUB$L_FLAGS = 0000001C
CLUB$L_LOCAL_CSB = 00000010
CLUB$Q_FTIME = 0000002C
CLUB$V_CLUSTER = 00000000
CLUB$W_NODES = 00000024
CLUB$W_QUORUM = 00000020

```

```

CLUB$W_VOTES = 00000022
COMPAT 000007B1 R 02
CSB$L_CSID = 0000004C
CSB$L_SB = 00000068
CSB$W_QUORUM = 00000052
CSB$W_VOTES = 00000050
CSID = 00000004
CSIDADR = 00000008
CSTRING = 00000002
CTL$GL_PCB ***** X 02
EFN = 00000004
EXES 000007FD R 02
EXESGETSYI 00000000 RG 03
EXESGL_ARCHFLAG ***** X 02
EXESGL_CLITABL ***** X 02
EXESGL_DEFFLAGS ***** X 02
EXESGL_DYNAMIC_FLAGS ***** X 02
EXESGL_LOCKRTRY ***** X 02
EXESGL_MSGFLAGS ***** X 02
EXESGL_RTMSPT ***** X 02
EXESGL_STATIC_FLAGS ***** X 02
EXESGL_SYSUIC ***** X 02
EXESGL_WSFLAGS ***** X 02
EXESGQ_BOOTTIME ***** X 02
EXESNAMCSID 00000AF1 R 02
EXESPROBEW ***** X 02
EXESV_BRK_DISUSER = 00000003
EXESV_BRK_TERM = 00000002
EXESV_BUGDUMP ***** X 02
EXESV_BUGREBOOT ***** X 02
EXESV_CJFLOAD ***** X 02
EXESV_CJFSYSRUJ ***** X 02
EXESV_CLASS_PROT = 00000000
EXESV_CONCEALED ***** X 02
EXESV_CRDENABL ***** X 02
EXESV_DISMOUMSG = 00000001 G 02
EXESV_FATAL_BUG ***** X 02
EXESV_MOUNTMSG = 00000000 G 02
EXESV_MULTACP ***** X 02
EXESV_NOAUTOCNF ***** X 02
EXESV_NOCLOCK ***** X 02
EXESV_NOCLUSTER ***** X 02
EXESV_OPAO = 00000000 G 02
EXESV_POOLPGING ***** X 02
EXESV_REBLDSYSD = 00000001
EXESV_RESALLOC ***** X 02
EXESV_SAVEDUMP ***** X 02
EXESV_SBIERR ***** X 02
EXESV_SETTIME ***** X 02
EXESV_SHRF11ACP ***** X 02
EXESV_SSINHIBIT ***** X 02
EXESV_SYSPAGING ***** X 02
EXESV_SYSUAFALT ***** X 02
EXESV_SYSWRTABL ***** X 02
EXESV_WRITESYSPARAMS = 00000001
EXESV_XQP_RESIDENT = 00000000
EXETBC 00000004 R 02

```

**F1

SYSGETSYI
Symbol table

B 10
- GET SYSTEM INFORMATION SYSTEM SERVICE 16-SEP-1984 02:10:18 VAX/VMS Macro V04-00
5-SEP-1984 03:54:07 [SYS.SRC]SYSGETSYI.MAR;1

Page 33
(6)

EXE_GETSYI	000006D7	R	02	PFL\$L_FREPAGECNT	= 00000018		
FETCH_CLU	00000957	R	02	PFL\$V_INITED	= 00000000		
FLAGS	= FFFFFFFC			POINT_R4	00000935	R	02
FLDS	00000808	R	02	PQL\$GDASTLM	*****	X	02
FLDTBL	0000050E	R	02	PQL\$GDBIOLM	*****	X	02
GETSYISW	= 00000000			PQL\$GDBYTLM	*****	X	02
GET_SB_FLD	00000950	R	02	PQL\$GDCPULM	*****	X	02
GOTCSID	00000BC5	R	02	PQL\$GDDIOLM	*****	X	02
GOTNAM	00000BB5	R	02	PQL\$GDENQLM	*****	X	02
GRET	0000076A	R	02	PQL\$GDFILLM	*****	X	02
IOC\$GW_LAMAPREG	*****	X	02	PQL\$GDJTQUOTA	*****	X	02
IOC\$GW_MAXBUF	*****	X	02	PQL\$GDPGFLQUOTA	*****	X	02
IOC\$GW_MBXBFQUO	*****	X	02	PQL\$GDPRCLM	*****	X	02
IOC\$GW_MBXMXMSG	*****	X	02	PQL\$GDTQELM	*****	X	02
IOC\$GW_MBXNMMSG	*****	X	02	PQL\$GDWSDEFAULT	*****	X	02
IOC\$GW_MVTIMEOUT	*****	X	02	PQL\$GDWSEXTENT	*****	X	02
IOC\$GW_XFMXRATE	*****	X	02	PQL\$GDWSQUOTA	*****	X	02
IOSB	= 00000014			PQL\$GMASTLM	*****	X	02
IPL\$ASTDEL	= 00000002			PQL\$GMBIOLM	*****	X	02
IPL\$SCS	= 00000008			PQL\$GMBYTLM	*****	X	02
ITMLST	= 00000010			PQL\$GMCPLM	*****	X	02
LCK\$GL_EXTRASTK	*****	X	02	PQL\$GMDIOLM	*****	X	02
LCK\$GL_HTBLSIZ	*****	X	02	PQL\$GMENQLM	*****	X	02
LCK\$GL_IDTBLMAX	*****	X	02	PQL\$GMFILLM	*****	X	02
LCK\$GL_IDTBLSIZ	*****	X	02	PQL\$GMJTQUOTA	*****	X	02
LCK\$GL_WAITTIME	*****	X	02	PQL\$GMPGFLQUOTA	*****	X	02
LNMSGL_HTBLSIZP	*****	X	02	PQL\$GMPRCLM	*****	X	02
LNMSGL_HTBLSIZS	*****	X	02	PQL\$GMTQELM	*****	X	02
LOCAL_SB	0000092A	R	02	PQL\$GMWSDEFAULT	*****	X	02
LOCAL_SPACE	= FFFFFFFE0			PQL\$GMWSEXTENT	*****	X	02
LOCK	0000098D	R	02	PQL\$GMWSQUOTA	*****	X	02
LOCKPAGE	00000BFD	R	02	PR\$S_SID_TYPE	= 00000008		
MAXCOUNT	00000000	R	02	PR\$V_SID_TYPE	= 00000018		
MAXSTRUC	= 00000002			PR\$TPL	= 00000012		
MAX_EXE_ITEM	= 00000101			PR\$SID	= 0000003E		
MAX_FLD_ITEM	= 0000002A			PSL\$S_PVRMOD	= 00000002		
MMG\$GL_MAXPFIDX	*****	X	02	PSL\$V_PVRMOD	= 00000016		
MMG\$GL_NULLPFL	*****	X	02	PUTDATA	00000846	R	02
MMG\$GL_PAGSWPVC	*****	X	02	RETURN	00000BE8	R	02
MMG\$GL_PHYPGCNT	*****	X	02	SBSB_HWVERS	= 00000038		
MPW\$GB_PRIO	*****	X	02	SBSB_SYSTEMID	= 00000018		
MPW\$GL_THRESH	*****	X	02	SBSQ_SWINCARN	= 0000002C		
MPW\$GL_WAITLIM	*****	X	02	SB\$T_HWTYPE	= 00000034		
MPW\$GW_HILIM	*****	X	02	SB\$T_NODENAME	= 00000044		
MPW\$GW_LOLIM	*****	X	02	SB\$T_SWTYPE	= 00000024		
MPW\$GW_MPWPC	*****	X	02	SB\$T_SWVERS	= 00000028		
NAMCSID	000009EE	R	02	SCH\$CLREF	*****	X	02
NODE	= 0000000C			SCH\$GL_AWSTIME	*****	X	02
NODENAME	= 00000008			SCH\$GL_BORROWLIM	*****	X	02
NONEX	00000BAB	R	02	SCH\$GL_CURPCB	*****	X	02
NULLARG1	= 00000008			SCH\$GL_GROWLIM	*****	X	02
NULLARG2	= 0000000C			SCH\$GL_PFRATH	*****	X	02
OUTLEN	= 00000004			SCH\$GL_PFRATL	*****	X	02
PCBSL_PID	= 00000060			SCH\$GL_PFRATS	*****	X	02
PCBSW_ASTCNT	= 00000038			SCH\$GL_SWPRATE	*****	X	02
PFL\$B_FLAGS	= 00000023			SCH\$GL_WSDEC	*****	X	02
PFL\$B_BITMAPSIZ	= 00000014			SCH\$GL_WSINC	*****	X	02

[illegible]

SYSGETSYI
Symbol table

- GET SYSTEM INFORMATION SYSTEM SERVICE D 10
16-SEP-1984 02:10:18 VAX/VMS Macro V04-00
5-SEP-1984 03:54:07 [SYS.SRC]SYSGETSYI.MAR;1

Page 35
(6)

SPECIAL_LEN	=	0000001A		
SPECIAL_SPACE	=	FFFFFFEC		
SS\$_ACCVIO	=	0000000C		
SS\$_BADPARAM	=	00000014		
SS\$_EXASTLM	=	00002A04		
SS\$_IVLOGNAM	=	00000154		
SS\$_NOMORENODE	=	00000A00		
SS\$_NORMAL	=	00000001		
SS\$_NOSUCHNODE	=	0000028C		
STEP	=	00000005		
SWP\$GB_Prio	*****		X	02
SWP\$GL_SWPPGCNT	*****		X	02
SWP\$GW_SWPINC	*****		X	02
SYIS_C_FLDTYPE	=	00000002		
SYIS_ACP_BASEPRIO	=	000010B5		
SYIS_ACP_DATACHECK	=	000010B4		
SYIS_ACP_DINDXCACHE	=	00001101		
SYIS_ACP_DIRCACHE	=	000010AA		
SYIS_ACP_EXTCACHE	=	000010AD		
SYIS_ACP_EXTLIMIT	=	000010AE		
SYIS_ACP_FIDCACHE	=	000010AC		
SYIS_ACP_HDRCACHE	=	000010A9		
SYIS_ACP_MAPCACHE	=	000010A8		
SYIS_ACP_MAXREAD	=	000010B1		
SYIS_ACP_MULTIPLE	=	00002005		
SYIS_ACP_QUOCACHE	=	000010AF		
SYIS_ACP_REBLDSYSD	=	00002029		
SYIS_ACP_SHARE	=	0000200C		
SYIS_ACP_SWAPFLGS	=	000010B6		
SYIS_ACP_SYSACC	=	000010B0		
SYIS_ACP_WINDOW	=	000010B2		
SYIS_ACP_WORKSET	=	000010AB		
SYIS_ACP_WRITEBACK	=	000010B3		
SYIS_ACP_XQP_RES	=	00002025		
SYIS_ALLOCLASS	=	000010E5		
SYIS_ARCHFLAG	=	000010DA		
SYIS_AWSMIN	=	00001038		
SYIS_AWSTIME	=	00001039		
SYIS_BALSETCNT	=	00001012		
SYIS_BJOBLIM	=	000010B9		
SYIS_BOOTTIME	=	000010BF		
SYIS_BORROWLIM	=	00001056		
SYIS_BUGCHECKFATAL	=	00002004		
SYIS_BUGREBOOT	=	00002001		
SYIS_CHANNELCNT	=	00001024		
SYIS_CHARACTER_EMULATED	=	0000201E		
SYIS_CJFLOAD	=	00002019		
SYIS_CJFSYSRUJ	=	0000201A		
SYIS_CLASS_PROT	=	0000201D		
SYIS_CLISYMTBL	=	0000105B		
SYIS_CLUSTER_FSYSID	=	000010CD		
SYIS_CLUSTER_FTIME	=	000010CE		
SYIS_CLUSTER_MEMBER	=	000010CF		
SYIS_CLUSTER_NODES	=	000010CA		
SYIS_CLUSTER_QUORUM	=	000010CC		
SYIS_CLUSTER_VOTES	=	000010CB		
SYIS_CONCEAL_DEVICES	=	00002012		

SYIS_CPU	=	00002000
SYIS_CRDENABLE	=	00002002
SYIS_CTLIMGLIM	=	00001027
SYIS_CTLPAGES	=	00001026
SYIS_DEADLOCK_WAIT	=	0000105E
SYIS_DECIMAL_EMULATED	=	0000201F
SYIS_DEFMBXBOFQUO	=	00001050
SYIS_DEFMBXMXMSG	=	00001051
SYIS_DEFMBXNUMMSG	=	00001052
SYIS_DEFPRI	=	000010B7
SYIS_DEFQUEPRI	=	000010E2
SYIS_DISK_QUORUM	=	000010DC
SYIS_DISMOUMSG	=	00002015
SYIS_DLCKEXTRASTK	=	00001011
SYIS_DORMANTWAIT	=	000010F1
SYIS_DUMPBUG	=	00002003
SYIS_D_FLOAT_EMULATED	=	00002020
SYIS_EXTRACPD	=	0000104C
SYIS_EXUSRSTK	=	0000101B
SYIS_FREEGOAL	=	00001054
SYIS_FREELIM	=	00001053
SYIS_F_FLOAT_EMULATED	=	00002021
SYIS_GBLPAGES	=	00001007
SYIS_GBLPAGFIL	=	00001008
SYIS_GBLSECTIONS	=	00001006
SYIS_GROWLIM	=	00001055
SYIS_G_FLOAT_EMULATED	=	00002022
SYIS_H_FLOAT_EMULATED	=	00002023
SYIS_IJOBLIM	=	000010B8
SYIS_IMGIOCNT	=	00001028
SYIS_INTSTKPAGES	=	00001010
SYIS_IOTA	=	0000103D
SYIS_IRPCOUNT	=	00001013
SYIS_IRPCOUNTV	=	00001014
SYIS_KFILSTCNT	=	00001005
SYIS_LAMAPREGS	=	00001059
SYIS_LASTEXE	=	00001102
SYIS_LASTFLD	=	0000202B
SYIS_LGI_BRK_DISUSER	=	00002028
SYIS_LGI_BRK_LIM	=	000010E8
SYIS_LGI_BRK_TERM	=	00002027
SYIS_LGI_BRK_TMO	=	000010E9
SYIS_LGI_HID_TIM	=	000010EA
SYIS_LGI_PWD_TMO	=	000010EB
SYIS_LGI_RETRY_LIM	=	000010E6
SYIS_LGI_RETRY_TMO	=	000010E7
SYIS_LNMPHASHTBL	=	00001072
SYIS_LNMSHASHTBL	=	00001071
SYIS_LOADCHKPRT	=	00002017
SYIS_LOADERAPT	=	00002016
SYIS_LOADMTACCESS	=	00002024
SYIS_LOCKDIRWT	=	000010EF
SYIS_LOCKIDTBL	=	0000105C
SYIS_LOCKIDTBL_MAX	=	000010C0
SYIS_LOCKRETRY	=	00001057
SYIS_LONGWAIT	=	0000103E
SYIS_LRPCOUNT	=	0000101C

SYS
V04-

SYSGETSYI
Symbol table

E 10
- GET SYSTEM INFORMATION SYSTEM SERVICE 16-SEP-1984 02:10:18 VAX/VMS Macro V04-00
5-SEP-1984 03:54:07 [SYS.SRC]SYSGETSYI.MAR;1

Page 36
(6)

SYIS_LRPCOUNTV = 0000101D
SYIS_LRPMIN = 0000101F
SYIS_LRPSIZE = 0000101E
SYIS_MAXBUF = 0000104F
SYIS_MAXPROCESSCNT = 00001009
SYIS_MAXQUEPRI = 000010E3
SYIS_MAXSYSGROUP = 0000104D
SYIS_MINWSCNT = 0000100C
SYIS_MOUNTMSG = 00002014
SYIS_MPW_HILIMIT = 0000102B
SYIS_MPW_LOLIMIT = 0000102C
SYIS_MPW_PRIO = 0000102D
SYIS_MPW_THRESH = 0000102F
SYIS_MPW_WAITLIMIT = 00001030
SYIS_MPW_WRTCLUSTER = 0000102A
SYIS_MVTIMEOUT = 0000104E
SYIS_NJOBLIM = 000010BA
SYIS_NOAUTOCONFIG = 00002006
SYIS_NOCLOCK = 00002007
SYIS_NOCLUSTER = 00002008
SYIS_NODENAME = 000010D9
SYIS_NODE_AREA = 0000201B
SYIS_NODE_CSID = 000010D0
SYIS_NODE_HWTYPE = 000010D7
SYIS_NODE_HWVERS = 000010D8
SYIS_NODE_NUMBER = 0000201C
SYIS_NODE_QUORUM = 000010D2
SYIS_NODE_SWINCARN = 000010D4
SYIS_NODE_SWTYPE = 000010D5
SYIS_NODE_SWVERS = 000010D6
SYIS_NODE_SYSTEMID = 000010D3
SYIS_NODE_VOTES = 000010D1
SYIS_NPAGEDYN = 00001016
SYIS_NPAGEVIR = 00001017
SYIS_OLDCPU = 00000200
SYIS_OLDSID = 00000201
SYIS_OLDVERSION = 00000100
SYIS_PAGEDYN = 00001018
SYIS_PAGEFILE_FREE = 000010F4
SYIS_PAGEFILE_PAGE = 000010F2
SYIS_PAGFILCNT = 0000100D
SYIS_PAGTBLPFC = 00001003
SYIS_PAMAXPORT = 000010E0
SYIS_PANOPOLL = 000010F8
SYIS_PANUMPOLL = 0000106C
SYIS_PAPOLLINTERVAL = 0000106D
SYIS_PAPOOLLINTERVAL = 0000106E
SYIS_PASANITY = 000010E1
SYIS_PASTDGBUF = 0000106B
SYIS_PASTIMOUT = 0000106A
SYIS_PE1 = 000010F9
SYIS_PE2 = 000010FA
SYIS_PE3 = 000010FB
SYIS_PE4 = 000010FC
SYIS_PE5 = 000010FD
SYIS_PE6 = 000010FE
SYIS_PFCDEFAULT = 00001002

SYIS_PFRATH = 00001034
SYIS_PFRATL = 00001033
SYIS_PFRATS = 00001035
SYIS_PHYSICALPAGES = 00001032
SYIS_PIOFAGES = 00001025
SYIS_PIXSCAN = 0000100A
SYIS_POOLPAGING = 00002009
SYIS_PQL_DASTLM = 0000108E
SYIS_PQL_DBIOLM = 00001090
SYIS_PQL_DBYTLM = 00001092
SYIS_PQL_DCPULM = 00001094
SYIS_PQL_DDIOIM = 00001096
SYIS_PQL_DENQLM = 000010A6
SYIS_PQL_DFILLM = 00001098
SYIS_PQL_DJTQUOTA = 000010EC
SYIS_PQL_DPGFLQUOTA = 0000109A
SYIS_PQL_DPRCLM = 0000109C
SYIS_PQL_DTQELM = 0000109E
SYIS_PQL_DWSDEFAULT = 000010A0
SYIS_PQL_DWSEXTENT = 000010A4
SYIS_PQL_DWSQUOTA = 000010A2
SYIS_PQL_MASTLM = 0000108F
SYIS_PQL_MBIOLM = 00001091
SYIS_PQL_MBYTLM = 00001093
SYIS_PQL_MCPULM = 00001095
SYIS_PQL_MDIOLM = 00001097
SYIS_PQL_MENQLM = 000010A7
SYIS_PQL_MFILLM = 00001099
SYIS_PQL_MJTQUOTA = 000010ED
SYIS_PQL_MPGFLQUOTA = 0000109B
SYIS_PQL_MPRCLM = 0000109D
SYIS_PQL_MTQELM = 0000109F
SYIS_PQL_MWSDEFAULT = 000010A1
SYIS_PQL_MWSEXTENT = 000010A5
SYIS_PQL_MWSQUOTA = 000010A3
SYIS_PRCPOLINTERVAL = 00001069
SYIS_PROCSECTCNT = 0000100B
SYIS_QDSKINTERVAL = 000010E4
SYIS_QDSKVOTES = 000010F0
SYIS_QUANTUM = 00001029
SYIS_QUORUM = 000010BC
SYIS_REALTIME SPTS = 0000105A
SYIS_RECIXNINTERVAL = 000010BE
SYIS_RESALLOC = 00002010
SYIS_RESHASHTBL = 0000105D
SYIS_RJOBLIM = 000010BB
SYIS_RMS_DFMBC = 00001084
SYIS_RMS_DFMBFHSH = 0000108A
SYIS_RMS_DFMBFIDX = 00001089
SYIS_RMS_DFMBFREL = 00001088
SYIS_RMS_DFMBFSDK = 00001085
SYIS_RMS_DFMBF SMT = 00001086
SYIS_RMS_DFMBF SUR = 00001087
SYIS_RMS_DFNBC = 00001100
SYIS_RMS_EXTEND SIZE = 0000108C
SYIS_RMS_FILEPROT = 0000108D
SYIS_RMS_GBLBUFQUO = 000010FF

SYS
V04-

SYIS-RMS PROLOGUE	= 0000108B
SYIS- SAVEDUMP	= 00002013
SYIS-SBIERRENABLE	= 0000200A
SYIS-SCSBUFFCNT	= 0000105F
SYIS-SCSCONNCNT	= 00001060
SYIS-SCSFLOWCUSH	= 00001064
SYIS-SCSMAXDG	= 00001062
SYIS-SCSMAXMSG	= 00001063
SYIS-SCSNODE	= 00001067
SYIS-SCSRESPCNT	= 0000106
SYIS-SCSSYSTEMID	= 00001065
SYIS-SCSSYSTEMIDH	= 00001066
SYIS-SCS EXISTS	= 000010DB
SYIS-SETTIME	= 0000200B
SYIS-SID	= 00001001
SYIS-SPTREQ	= 0000101A
SYIS-SRPCOUNT	= 00001020
SYIS-SRPCOUNTV	= 00001021
SYIS-SRPMIN	= 00001023
SYIS-SRPSIZE	= 00001022
SYIS-SSINHIBIT	= 00002011
SYIS-STARTUP_P1	= 000010C2
SYIS-STARTUP_P2	= 000010C3
SYIS-STARTUP_P3	= 000010C4
SYIS-STARTUP_P4	= 000010C5
SYIS-STARTUP_P5	= 000010C6
SYIS-STARTUP_P6	= 000010C7
SYIS-STARTUP_P7	= 000010C8
SYIS-STARTUP_P8	= 000010C9
SYIS-SWAPFILE_FREE	= 000010F5
SYIS-SWAPFILE_PAGE	= 000010F3
SYIS-SWPALLOCINC	= 0000103C
SYIS-SWPFail	= 0000103F
SYIS-SWPFILCNT	= 0000100E
SYIS-SWPOUTPGCNT	= 0000103B
SYIS-SWPRATE	= 0000103A
SYIS-SWP_Prio	= 0000102E
SYIS-SYSMWCNT	= 0000100F
SYIS-SYSPAGING	= 0000200D
SYIS-SYSPFC	= 00001004
SYIS-TAILORED	= 000010C1
SYIS-TBSKIPWSL	= 00001031
SYIS-TIMEPROMPTWAIT	= 0000106F
SYIS-TTY_ALTALARM	= 0000107D
SYIS-TTY_ALTYPAHD	= 0000107C
SYIS-TTY_AUTOCHAR	= 000010F7
SYIS-TTY_BUF	= 00001078
SYIS-TTY_CLASSNAME	= 00001081
SYIS-TTY_DEFCHAR	= 00001079
SYIS-TTY_DEFCHAR2	= 0000107A
SYIS-TTY_DEFPORT	= 00001083
SYIS-TTY_DIALTYPE	= 00001074
SYIS-TTY_DMASIZE	= 0000107E
SYIS-TTY_OWNER	= 00001080
SYIS-TTY_PARITY	= 00001077
SYIS-TTY_PROT	= 0000107F
SYIS-TTY_RSPEED	= 00001076

SYIS-TTY-SCANDELTA	=	00001073		
SYIS-TTY-SILOTIME	=	00001082		
SYIS-TTY-SPEED	=	00001075		
SYIS-TTY-TIMEOUT	=	000010F6		
SYIS-TTY-TYPAHDSZ	=	0000107B		
SYIS-UAFALTERNATE	=	0000200E		
SYIS-UDABURSTRATE	=	00001070		
SYIS-USER3	=	0000104A		
SYIS-USER4	=	0000104B		
SYIS-USERD1	=	00001048		
SYIS-USERD2	=	00001049		
SYIS-VAXCLUSTER	=	000010EE		
SYIS-VERSION	=	00001000		
SYIS-VIRTUALPAGECNT	=	00001019		
SYIS-VMS5	=	00001044		
SYIS-VMS6	=	00001045		
SYIS-VMS7	=	00001046		
SYIS-VMS8	=	00001047		
SYIS-VMSD1	=	00001040		
SYIS-VMSD2	=	00001041		
SYIS-VMSD3	=	00001042		
SYIS-VMSD4	=	00001043		
SYIS-VOTES	=	000010BD		
SYIS-WRITABLESYS	=	0000200F		
SYIS-WRITESYSPARAMS	=	00002026		
SYIS-WSDEC	=	00001037		
SYIS-WSINC	=	00001036		
SYIS-WSMAX	=	00001015		
SYIS-WS_OPAO	=	0000202A		
SYIS-XFMAXRATE	=	00001058		
SYI_BIT	=	00000004		
SYI-S_INCLUSTER	=	00000001		
SYI-S-REMOTE_NODE	=	00000001		
SYI-S-RETIRED	=	00000001		
SYI-S-WILD	=	00000001		
SYI-V_INCLUSTER	=	00000001		
SYI-V-REMOTE_NODE	=	00000002		
SYI-V-RETIRED	=	00000003		
SYI-V-WILD	=	00000000		
SYSSDCLAST	*****			
SYSSGB_BRK_LIM	*****		GX	02
SYSSGB_DEFPRI	*****		X	02
SYSSGB_DEFQUEPRI	*****		X	02
SYSSGB_DFMBC	*****		X	02
SYSSGB_DFMBFHSH	*****		X	02
SYSSGB_DFMBFIDX	*****		X	02
SYSSGB_DFMBFREL	*****		X	02
SYSSGB_DFMBFSDK	*****		X	02
SYSSGB_DFMBFSMT	*****		X	02
SYSSGB_DFMBFSUR	*****		X	02
SYSSGB_DFNBC	*****		X	02
SYSSGB_MAXQUEPRI	*****		X	02
SYSSGB_PWD_TMO	*****		X	02
SYSSGB_RETRY_LIM	*****		X	02
SYSSGB_RETRY_TMO	*****		X	02
SYSSGB_RMSPROLOG	*****		X	02
SYSSGL_BRK_TMO	*****		X	02

SYSGETSYI
Symbol table

G 10
- GET SYSTEM INFORMATION SYSTEM SERVICE

16-SEP-1984 02:10:18
5-SEP-1984 03:54:07

VAX/VMS Macro V04-00
[SYS.SRC]SYSGETSYI.MAR;1

Page 38
(6)

```
SYSSGL_HID_TIM      ***** X 02
SYSSGL_VERSION      ***** X 02
SYSSGW_BJOBLIM      ***** X 02
SYSSGW_FILEPROT     ***** X 02
SYSSGW_GBLBUFQUO    ***** X 02
SYSSGW_IJOBLIM      ***** X 02
SYSSGW_NJOBLIM      ***** X 02
SYSSGW_RJOBLIM      ***** X 02
SYSSGW_RMSEXTEND     ***** X 02
TEMPORARY           = FFFFFFFE8
TTY$GB_AUTOCHAR     ***** X 02
TTY$GB_DEFSPEED     ***** X 02
TTY$GB_DIALTYP      ***** X 02
TTY$GB_PARITY       ***** X 02
TTY$GB_RSPEED       ***** X 02
TTY$GB_SILOTIME     ***** X 02
TTY$GL_DEFCHAR      ***** X 02
TTY$GL_DEFCHAR2     ***** X 02
TTY$GL_DEFPOR       ***** X 02
TTY$GL_DELTA        ***** X 02
TTY$GL_OWNUIC       ***** X 02
TTY$GL_TIMEOUT      ***** X 02
TTY$GW_ALTALARM     ***** X 02
TTY$GW_ALTPAHD      ***** X 02
TTY$GW_CLASSNAM     ***** X 02
TTY$GW_DEFBUF       ***** X 02
TTY$GW_DMASIZE      ***** X 02
TTY$GW_PROT         ***** X 02
TTY$GW_TYPAHDSZ     ***** X 02
VALUE               = 00000000
VERIFY_CSB          = 00000964 R 02
XTYPE               = 00000001
```

+-----+
! Psect synopsis !
+-----+

PSECT name	Allocation	PSECT No.	Attributes
. ABS .	00000000 (0.)	00 (0.)	NOPIC USR CON ABS LCL NOSHR NOEXE NORD NOWRT NOVEC BYTE
\$ABSS	00000000 (0.)	01 (1.)	NOPIC USR CON ABS LCL NOSHR EXE RD WRT NOVEC BYTE
YF\$\$\$SYSGETSYI	00000BFE (3070.)	02 (2.)	NOPIC USR CON REL LCL NOSHR EXE RD WRT NOVEC BYTE
YEXEPAGED	00000005 (5.)	03 (3.)	NOPIC USR CON REL LCL NOSHR EXE RD WRT NOVEC BYTE
AEXENONPAGED	0000000A (10.)	04 (4.)	NOPIC USR CON REL LCL NOSHR EXE RD WRT NOVEC BYTE

+-----+
! Performance indicators !
+-----+

Phase	Page faults	CPU Time	Elapsed Time
Initialization	39	00:00:00.06	00:00:00.59
Command processing	130	00:00:00.70	00:00:04.42
Pass 1	1222	00:01:21.37	00:03:18.24
Symbol table sort	0	00:00:02.71	00:00:06.24
Pass 2	790	00:00:16.21	00:00:37.57
Symbol table output	83	00:00:00.52	00:00:01.89

Psect synopsis output	2	00:00:00.02	00:00:00.02
Cross-reference output	0	00:00:00.00	00:00:00.00
Assembler run totals	2268	00:01:41.60	00:04:08.98

The working set limit was 3000 pages.

439180 bytes (858 pages) of virtual memory were used to buffer the intermediate code.

There were 100 pages of symbol table space allocated to hold 1682 non-local and 67 local symbols.

1428 source lines were read in Pass 1, producing 54 object records in Pass 2.

136 pages of virtual memory were used to define 37 macros.

! Macro library statistics !

Macro library name	Macros defined
-----	-----
-\$255\$DUA28:[SYSLIB]SYSBLDMLB.MLB;1	5
-\$255\$DUA28:[SYS.OBJ]LIB.MLB;1	14
-\$255\$DUA28:[SYSLIB]STARLET.MLB;2	12
TOTALS (all libraries)	31

4130 GETS were required to define 31 macros.

There were no errors, warnings or information messages.

MACRO/LIS=LIS\$:SYSGETSYI/OBJ=OBJ\$:SYSGETSYI MSRC\$:SYSGETSYI/UPDATE=(ENH\$:SYSGETSYI)+EXECML\$/LIB+SYS\$LIBRARY:SYSBLDMLB/LIB

0385

DIGITAL EQUIPMENT CORPORATION
CONFIDENTIAL AND PROPRIETARY